



Glavno

Range	Prisma
Range compatibility	Prisma G
Product or component type	Rail
Accessory / separate part category	Installation accessory
Type of rail	Modular Adjustable
Installed device	TeSys: fixed GV3 TeSys: fixed GV2L TeSys: fixed GV2P Compact: fixed NG160 with earth leakage protection - control: toggle Compact: fixed NG160 without earth leakage protection - control: toggle Compact: fixed NG160 NA without earth leakage protection - control: toggle Compact: fixed NSXm without earth leakage protection - control: toggle - vertical installation Compact: fixed NSXm with earth leakage protection - control: toggle - vertical installation
Poles description	9 x 3P: fixed: GV2L 9 x 3P: fixed: GV2P 1 x 3P: fixed: NG160 1 x 3P: fixed: NG160 NA 7 x 3P: fixed: GV3 1 x 4P: fixed: NG160 1 x 4P: fixed: NG160 NA 1 x 3P or 4P: fixed: NSXm vertical installation

Komplementarno

Enclosure/cubicle description	Floor-standing enclosure - width 600 mm Wall-mounted enclosure - width 600 mm
Number of vertical modules [50 mm]	3 module(s) : GV2L , direct in 600 mm Wide floor-standing enclosure 3 module(s) : GV2L , direct in 600 mm Wide wall-mounted enclosure 3 module(s) : GV2P , direct in 600 mm Wide floor-standing enclosure 3 module(s) : GV2P , direct in 600 mm Wide wall-mounted enclosure 5 module(s) : GV3 , direct in 600 mm Wide floor-standing enclosure 5 module(s) : GV3 , direct in 600 mm Wide wall-mounted enclosure 5 module(s) : NG160 without earth leakage protection , direct in 600 mm Wide floor-standing enclosure 5 module(s) : NG160 without earth leakage protection , direct in 600 mm Wide wall-mounted enclosure 5 module(s) : NG160 NA without earth leakage protection , direct in 600 mm Wide floor-standing enclosure 5 module(s) : NG160 NA without earth leakage protection , direct in 600 mm Wide wall-mounted enclosure 7 module(s) : NSXm without earth leakage protection , direct in 600 mm Wide floor-standing enclosure 7 module(s) : NSXm without earth leakage protection , direct in 600 mm Wide wall-mounted enclosure 7 module(s) : NSXm without earth leakage protection , connection block in 600 mm Wide floor-standing enclosure 7 module(s) : NSXm without earth leakage protection , connection block in 600 mm Wide wall-mounted enclosure 5 module(s) : NG160 with earth leakage protection , direct in 600 mm Wide floor-standing enclosure 5 module(s) : NG160 with earth leakage protection , direct in 600 mm Wide wall-mounted enclosure 7 module(s) : NSXm with earth leakage protection , direct in 600 mm Wide floor-standing enclosure 7 module(s) : NSXm with earth leakage protection , direct in 600 mm Wide wall-

Informacije dane u ovoj dokumentaciji sadrže opće opise i/ili tehničke karakteristike o performansama ovdje sadržanih proizvoda. Ova dokumentacija nije namijenjena kao zamjena za niti bi se trebala koristiti za određivanje prikladnosti ili pouzdanosti predmetnih proizvoda za konkretne korisničke primjene. Svaki takav korisnik ili integrator dužan je provesti odgovarajuću i poplunu analizu rizika, procjenu i ispitivanje proizvoda u odnosu na odgovarajuću specifičnu primjenu ili uporabu istog. Niti društvo Schneider Electric Industries SAS niti bilo koje od njegovih povezanih podružnica nećete preuzeti obvezu ili snositi odgovornost za pogrešnu upotrebu ovdje sadržanih informacija.

mounted enclosure
7 module(s) : NSXm with earth leakage protection , connection block in 600 mm
Wide floor-standing enclosure
7 module(s) : NSXm with earth leakage protection , connection block in 600 mm
Wide wall-mounted enclosure

9 mm pitches	48
Quantity per set	Set of 1
Width	600 mm
Product weight	0.34 kg
Colour	Grey
Material	Metal

Okolina

standards	IEC 61439-2 IEC 61439-1
product certifications	ASEFA

Offer Sustainability

Green Premium product	Green Premium product
Compliant - since 0807 - Schneider Electric declaration of conformity	Compliant - since 0807 - Schneider Electric declaration of conformity
Reference not containing SVHC above the threshold	Reference not containing SVHC above the threshold
Available	Available
Need no specific recycling operations	Need no specific recycling operations

Contractual warranty

Warranty period	18 months
-----------------	-----------