



Glavno

| | |
|------------------------------------|--|
| Range | Prisma |
| Range compatibility | Prisma G Pack 160 |
| Product or component type | Rail |
| Accessory / separate part category | Installation accessory |
| Type of rail | Modular Rear |
| Installed device | Altistart: ATS01N103/106FT TeSys: fixed GV2 + D or K contactors <= 40 A - horizontal installation TeSys: fixed TeSys U - horizontal installation TeSys: fixed GV3Pxx1 + LC1D40 to D65 - horizontal installation TeSys: fixed D or K contactors <= 40 A - horizontal installation |
| Poles description | 9 x 3P: fixed: GV2 + D or K contactors <= 40 A horizontal installation 9 x 3P: fixed: TeSys U horizontal installation 7 x 3P: fixed: GV3Pxx1 + LC1D40 to D65 horizontal installation 9 x 4P: fixed: D or K contactors <= 40 A horizontal installation |

Komplementarno

| | |
|------------------------------------|---|
| Enclosure/cubicle description | Floor-standing enclosure - width 600 mm Wall-mounted enclosure - width 600 mm Pack enclosure - width 555 mm |
| Number of vertical modules [50 mm] | 4 module(s) : ATS01N103/106FT in 600 mm Wide floor-standing enclosure 4 module(s) : ATS01N103/106FT in 600 mm Wide wall-mounted enclosure 4 module(s) : ATS01N103/106FT in 555 mm Wide Pack enclosure 3 module(s) : D or K contactors <= 40 A , direct in 600 mm Wide floor-standing enclosure 3 module(s) : D or K contactors <= 40 A , direct in 600 mm Wide wall-mounted enclosure 3 module(s) : D or K contactors <= 40 A , direct in 555 mm Wide Pack enclosure 5 module(s) : GV2 + D or K contactors <= 40 A , direct in 600 mm Wide floor-standing enclosure 5 module(s) : GV2 + D or K contactors <= 40 A , direct in 600 mm Wide wall-mounted enclosure 5 module(s) : GV2 + D or K contactors <= 40 A , direct in 555 mm Wide Pack enclosure 7 module(s) : GV3Pxx1 + LC1D40 to D65 , direct in 600 mm Wide floor-standing enclosure 7 module(s) : GV3Pxx1 + LC1D40 to D65 , direct in 600 mm Wide wall-mounted enclosure 7 module(s) : GV3Pxx1 + LC1D40 to D65 , direct in 555 mm Wide Pack enclosure 5 module(s) : TeSys U , direct in 600 mm Wide floor-standing enclosure 5 module(s) : TeSys U , direct in 600 mm Wide wall-mounted enclosure 5 module(s) : TeSys U , direct in 555 mm Wide Pack enclosure 4 module(s) : TeSys U , direct in 600 mm Wide floor-standing enclosure 4 module(s) : TeSys U , direct in 600 mm Wide wall-mounted enclosure 4 module(s) : TeSys U , direct in 555 mm Wide Pack enclosure |
| 9 mm pitches | 48 |
| Quantity per set | Set of 1 |
| Height | 14.8 mm |
| Width | 600 mm |
| Depth | 128 mm |

Informacije dane u ovoj dokumentaciji sadrže opće opisne i/ili tehničke karakteristike o performansama ovdje sadržanih proizvoda.
Ova dokumentacija nije namijenjena kao zamjena za niti bi se trebala koristiti za određivanje prikladnosti ili pouzdanosti predmetnih proizvoda za konkretne korisničke primjene.
Svaki takav korisnik ili integrator dužan je provesti odgovarajuću i potpunu analizu rizika, procjenu i ispitivanje proizvoda u odnosu na odgovarajuću specifičnu primjenu ili uporabu istog.
Niti društvo Schneider Electric Industries SAS niti bilo koje od njegovih povezanih podružnica neće preuzeti obvezu ili snositi odgovornost za pogrešnu upotrebu ovdje sadržanih informacija.

| | |
|----------------|---------|
| Product weight | 0.16 kg |
| Colour | Grey |
| Material | Metal |

Okolina

| | |
|------------------------|----------------------------|
| standards | IEC 61439-2 IEC 61439-1 |
| product certifications | ASEFA |

Offer Sustainability

| | |
|---|---|
| Green Premium product | Green Premium product |
| Compliant - since 0807 - Schneider Electric declaration of conformity | Compliant - since 0807 - Schneider Electric declaration of conformity |
| Reference not containing SVHC above the threshold | Reference not containing SVHC above the threshold |
| Available | Available |
| Need no specific recycling operations | Need no specific recycling operations |

Contractual warranty

| | |
|-----------------|-----------|
| Warranty period | 18 months |
|-----------------|-----------|