



### Glavno

Range	Prisma
Range compatibility	Prisma G
Product or component type	Rail
Accessory / separate part category	Installation accessory
Type of rail	Modular
Installed device	Multi 9: fixed modular device Acti 9: fixed modular device TeSys: fixed GV2LE TeSys: fixed GV2ME TeSys: fixed GV2RTn Multi 9: fixed modular device <= 40 A Acti 9: fixed modular device <= 40 A Multi 9: fixed NG125 with earth leakage protection - control: toggle Multi 9: fixed NG125 without earth leakage protection - control: toggle Multi 9: fixed NG125 NA - control: toggle Acti 9: fixed C120 with earth leakage protection - control: toggle Acti 9: fixed C120 without earth leakage protection - control: toggle Compact: fixed INS40 - control: direct front rotary handle - vertical installation Compact: fixed INS63 - control: direct front rotary handle - vertical installation Compact: fixed INS100 - control: direct front rotary handle - vertical installation Compact: fixed INS125 - control: direct front rotary handle - vertical installation Compact: fixed INS160 - control: direct front rotary handle - vertical installation Acti 9: fixed iC120 with earth leakage protection - control: toggle Acti 9: fixed iC120 without earth leakage protection - control: toggle
Poles description	1 x 3P: fixed: NG125 1 x 3P: fixed: NG125 NA 1 x 3P: fixed: C120 1 x 4P: fixed: NG125 1 x 4P: fixed: NG125 NA 1 x 4P: fixed: C120 1 x 3P: fixed: INS40 vertical installation 1 x 3P: fixed: INS63 vertical installation 1 x 3P: fixed: INS100 vertical installation 1 x 3P: fixed: INS125 vertical installation 1 x 3P: fixed: INS160 vertical installation 1 x 3P: fixed: iC120 1 x 4P: fixed: INS40 vertical installation 1 x 4P: fixed: INS63 vertical installation 1 x 4P: fixed: INS100 vertical installation 1 x 4P: fixed: INS125 vertical installation 1 x 4P: fixed: INS160 vertical installation 1 x 4P: fixed: iC120 4 x 3P: fixed: GV2LE 4 x 3P: fixed: GV2ME 4 x 3P: fixed: GV2RTn

### Komplementarno

Enclosure/cubicle description	Floor-standing duct - width 300 mm Wall-mounted duct - width 300 mm
-------------------------------	--

Informacije dane u ovoj dokumentaciji sadrže opće opise i/ili tehničke karakteristike o performansama ovdje sadržanih proizvoda.  
Ova dokumentacija nije namijenjena kao zamjena za niti bi se trebala koristiti za određivanje prikladnosti ili pouzdanosti predmetnih proizvoda za konkretne korisničke primjene.  
Svaki takav korisnik ili integrator dužan je provesti odgovarajuću i potpunu analizu rizika, procjenu i ispitivanje proizvoda u odnosu na odgovarajuću specifičnu primjenu ili uporabu istog.  
Niti društvo Schneider Electric, Industries SAS niti bilo koje od njegovih povezanih poduzeća ili podružnica neće preuzeti obvezu ili snositi odgovornost za pogrešnu upotrebu ovdje sadržanih informacija.

Number of vertical modules [50 mm]

4 module(s) : C120 without earth leakage protection , direct in 300 mm Wide floor-standing duct  
 4 module(s) : C120 without earth leakage protection , direct in 300 mm Wide wall-mounted duct  
 3 module(s) : GV2LE , direct in 300 mm Wide floor-standing duct  
 3 module(s) : GV2LE , direct in 300 mm Wide wall-mounted duct  
 3 module(s) : GV2ME , direct in 300 mm Wide floor-standing duct  
 3 module(s) : GV2ME , direct in 300 mm Wide wall-mounted duct  
 3 module(s) : GV2RTn , direct in 300 mm Wide floor-standing duct  
 3 module(s) : GV2RTn , direct in 300 mm Wide wall-mounted duct  
 4 module(s) : iC120 without earth leakage protection , direct in 300 mm Wide floor-standing duct  
 4 module(s) : iC120 without earth leakage protection , direct in 300 mm Wide wall-mounted duct  
 4 module(s) : INS100 , direct in 300 mm Wide floor-standing duct  
 4 module(s) : INS100 , direct in 300 mm Wide wall-mounted duct  
 5 module(s) : INS100 , direct in 300 mm Wide floor-standing duct  
 5 module(s) : INS100 , direct in 300 mm Wide wall-mounted duct  
 4 module(s) : INS125 , direct in 300 mm Wide floor-standing duct  
 4 module(s) : INS125 , direct in 300 mm Wide wall-mounted duct  
 5 module(s) : INS125 , direct in 300 mm Wide floor-standing duct  
 5 module(s) : INS125 , direct in 300 mm Wide wall-mounted duct  
 4 module(s) : INS160 , direct in 300 mm Wide floor-standing duct  
 4 module(s) : INS160 , direct in 300 mm Wide wall-mounted duct  
 5 module(s) : INS160 , direct in 300 mm Wide floor-standing duct  
 5 module(s) : INS160 , direct in 300 mm Wide wall-mounted duct  
 4 module(s) : INS40 , direct in 300 mm Wide floor-standing duct  
 4 module(s) : INS40 , direct in 300 mm Wide wall-mounted duct  
 4 module(s) : INS63 , direct in 300 mm Wide floor-standing duct  
 4 module(s) : INS63 , direct in 300 mm Wide wall-mounted duct  
 3 module(s) : modular device <= 40 A , direct in 300 mm Wide floor-standing duct  
 3 module(s) : modular device <= 40 A , direct in 300 mm Wide wall-mounted duct  
 4 module(s) : modular device , direct in 300 mm Wide floor-standing duct  
 4 module(s) : modular device , direct in 300 mm Wide wall-mounted duct  
 4 module(s) : NG125 without earth leakage protection , direct in 300 mm Wide floor-standing duct  
 4 module(s) : NG125 without earth leakage protection , direct in 300 mm Wide wall-mounted duct  
 4 module(s) : NG125 NA , direct in 300 mm Wide floor-standing duct  
 4 module(s) : NG125 NA , direct in 300 mm Wide wall-mounted duct  
 4 module(s) : C120 with earth leakage protection , direct in 300 mm Wide floor-standing duct  
 4 module(s) : C120 with earth leakage protection , direct in 300 mm Wide wall-mounted duct  
 4 module(s) : iC120 with earth leakage protection , direct in 300 mm Wide floor-standing duct  
 4 module(s) : iC120 with earth leakage protection , direct in 300 mm Wide wall-mounted duct  
 4 module(s) : NG125 with earth leakage protection , direct in 300 mm Wide floor-standing duct  
 4 module(s) : NG125 with earth leakage protection , direct in 300 mm Wide wall-mounted duct

9 mm pitches	20
Quantity per set	Set of 1
Height	93.5 mm
Width	300 mm
Depth	50 mm
Product weight	0.14 kg
Colour	Grey
Material	Metal

## Okolina

standards	IEC 61439-2 IEC 61439-1
product certifications	ASEFA

## Offer Sustainability

Green Premium product	Green Premium product
Compliant - since 0807 - Schneider Electric declaration of conformity	Compliant - since 0807 - Schneider Electric declaration of conformity
Reference not containing SVHC above the threshold	Reference not containing SVHC above the threshold

Available

Available

Need no specific recycling operations

Need no specific recycling operations

---

### Contractual warranty

Warranty period

18 months

---