



Glavno

Range	Prisma
Range compatibility	Prisma G
Product or component type	Rail
Accessory / separate part category	Installation accessory
Type of rail	Modular Adjustable
Installed device	TeSys: fixed GV3 Altistart: ATS01N103/106FT TeSys: fixed GV2L TeSys: fixed GV2P Compact: fixed NG160 without earth leakage protection - control: toggle TeSys: fixed GV2 + D or K contactors <= 40 A - horizontal installation TeSys: fixed TeSys U - horizontal installation TeSys: fixed GV3Pxx1 + LC1D40 to D65 - horizontal installation TeSys: fixed D or K contactors <= 40 A - horizontal installation Compact: fixed NG160 NA without earth leakage protection - control: toggle Compact: fixed NSXm without earth leakage protection - control: toggle - vertical installation Compact: fixed NSXm with earth leakage protection - control: toggle - vertical installation
Poles description	1 x 3P: fixed: NG160 1 x 3P: fixed: NG160 NA 1 x 4P: fixed: NG160 1 x 4P: fixed: NG160 NA 4 x 3P: fixed: GV2L 4 x 3P: fixed: GV2P 3 x 3P: fixed: GV3 4 x 3P: fixed: GV2 + D or K contactors <= 40 A horizontal installation 3 x 3P: fixed: GV3Pxx1 + LC1D40 to D65 horizontal installation 4 x 3P: fixed: TeSys U horizontal installation 4 x 4P: fixed: D or K contactors <= 40 A horizontal installation 1 x 3P or 4P: fixed: NSXm vertical installation

Komplementarno

Enclosure/cubicle description	Floor-standing duct - width 300 mm Wall-mounted duct - width 300 mm
Number of vertical modules [50 mm]	4 module(s) : ATS01N103/106FT in 300 mm Wide floor-standing duct 4 module(s) : ATS01N103/106FT in 300 mm Wide wall-mounted duct 3 module(s) : D or K contactors <= 40 A , direct in 300 mm Wide floor-standing duct 3 module(s) : D or K contactors <= 40 A , direct in 300 mm Wide wall-mounted duct 5 module(s) : GV2 + D or K contactors <= 40 A , direct in 300 mm Wide floor-standing duct 5 module(s) : GV2 + D or K contactors <= 40 A , direct in 300 mm Wide wall-mounted duct 3 module(s) : GV2L , direct in 300 mm Wide floor-standing duct 3 module(s) : GV2L , direct in 300 mm Wide wall-mounted duct 3 module(s) : GV2P , direct in 300 mm Wide floor-standing duct 3 module(s) : GV2P , direct in 300 mm Wide wall-mounted duct 5 module(s) : GV3 , direct in 300 mm Wide floor-standing duct 5 module(s) : GV3 , direct in 300 mm Wide wall-mounted duct 7 module(s) : GV3Pxx1 + LC1D40 to D65 , direct in 300 mm Wide floor-standing duct 7 module(s) : GV3Pxx1 + LC1D40 to D65 , direct in 300 mm Wide wall-mounted duct

Informacije dane u ovoj dokumentaciji sadrže opće opise i/ili tehničke karakteristike o performansama ovdje sadržanih proizvoda. Ova dokumentacija nije namijenjena kao zamjena za niti bi se trebala koristiti za određivanje prikladnosti ili pouzdanosti predmetnih proizvoda za konkretne korisničke primjene. Svaki takav korisnik ili integrator dužan je provesti odgovarajuću i potpunu analizu rizika, procjenu i ispitivanje proizvoda u odnosu na odgovarajuću specifičnu primjenu ili uporabu istog. Niti društvo Schneider Electric Industries SAS niti bilo koje od njegovih povezanih poduzeća ili podružnica neće preuzeti obvezu ili snositi odgovornost za pogrešnu upotrebu ovdje sadržanih informacija.

5 module(s) : NG160 without earth leakage protection , direct in 300 mm Wide floor-standing duct
 5 module(s) : NG160 without earth leakage protection , direct in 300 mm Wide wall-mounted duct
 5 module(s) : NG160 NA without earth leakage protection , direct in 300 mm Wide floor-standing duct
 5 module(s) : NG160 NA without earth leakage protection , direct in 300 mm Wide wall-mounted duct
 7 module(s) : NSXm without earth leakage protection , direct in 300 mm Wide floor-standing duct
 7 module(s) : NSXm without earth leakage protection , direct in 300 mm Wide wall-mounted duct
 7 module(s) : NSXm without earth leakage protection , connection block in 300 mm Wide floor-standing duct
 7 module(s) : NSXm without earth leakage protection , connection block in 300 mm Wide wall-mounted duct
 5 module(s) : TeSys U , direct in 300 mm Wide floor-standing duct
 5 module(s) : TeSys U , direct in 300 mm Wide wall-mounted duct
 4 module(s) : TeSys U , direct in 300 mm Wide floor-standing duct
 4 module(s) : TeSys U , direct in 300 mm Wide wall-mounted duct
 7 module(s) : NSXm with earth leakage protection , direct in 300 mm Wide floor-standing duct
 7 module(s) : NSXm with earth leakage protection , direct in 300 mm Wide wall-mounted duct
 7 module(s) : NSXm with earth leakage protection , connection block in 300 mm Wide floor-standing duct
 7 module(s) : NSXm with earth leakage protection , connection block in 300 mm Wide wall-mounted duct

9 mm pitches	20
Quantity per set	Set of 1
Width	300 mm
Product weight	0.18 kg
Colour	Grey
Material	Metal

Okolina

standards	IEC 61439-2 IEC 61439-1
product certifications	ASEFA

Offer Sustainability

Green Premium product	Green Premium product
Compliant - since 0807 - Schneider Electric declaration of conformity	Compliant - since 0807 - Schneider Electric declaration of conformity
Reference not containing SVHC above the threshold	Reference not containing SVHC above the threshold
Available	Available
Need no specific recycling operations	Need no specific recycling operations

Contractual warranty

Warranty period	18 months
-----------------	-----------