



Glavno

Range	Prisma
Range compatibility	Prisma G Prisma Pack 250
Product or component type	Mounting plate
Accessory / separate part category	Installation accessory
Installed device	Compact: fixed INS250 - control: direct front rotary handle - horizontal installation Compact: fixed INV250 - control: direct front rotary handle - horizontal installation Easypact: fixed CVS100...160 without earth leakage protection - control: toggle - horizontal installation Easypact: fixed CVS250 without earth leakage protection - control: toggle - horizontal installation Compact: fixed INV100 - control: direct front rotary handle - horizontal installation Compact: fixed INV160 - control: direct front rotary handle - horizontal installation Compact: fixed INV200 - control: direct front rotary handle - horizontal installation Compact: fixed NSX100...160 without earth leakage protection - control: toggle - horizontal installation Compact: fixed NSX250 without earth leakage protection - control: toggle - horizontal installation
Poles description	1 x 3P: fixed: NSX100...160 horizontal installation 1 x 4P: fixed: NSX100...160 horizontal installation 1 x 3P: fixed: NSX250 horizontal installation 1 x 4P: fixed: NSX250 horizontal installation 1 x 4P: fixed: CVS100...160 horizontal installation 1 x 3P: fixed: CVS100...160 horizontal installation 1 x 4P: fixed: CVS250 horizontal installation 1 x 3P: fixed: CVS250 horizontal installation 1 x 3P: fixed: INS250 horizontal installation 1 x 4P: fixed: INS250 horizontal installation 1 x 3P: fixed: INV100 horizontal installation 1 x 4P: fixed: INV100 horizontal installation 1 x 3P: fixed: INV250 horizontal installation 1 x 4P: fixed: INV250 horizontal installation 1 x 3P: fixed: INV160 horizontal installation 1 x 4P: fixed: INV160 horizontal installation 1 x 3P: fixed: INV200 horizontal installation 1 x 4P: fixed: INV200 horizontal installation

Komplementarno

Enclosure/cubicle description	Floor-standing enclosure - width 600 mm Wall-mounted enclosure - width 600 mm Floor-standing enclosure - width 850 mm Pack enclosure - width 600 mm Floor-standing enclosure + duct - width 600 + 300 mm Wall-mounted enclosure + duct - width 600 + 300 mm
Number of vertical modules [50 mm]	5 module(s) : CVS100...160 without earth leakage protection , direct with long terminal shield in 600 mm Wide floor-standing enclosure (cable coming from top or bottom of enclosure) 5 module(s) : CVS100...160 without earth leakage protection , direct with long terminal shield in 600 mm Wide wall-mounted enclosure (cable coming from top or bottom of enclosure) 4 module(s) : CVS100...160 without earth leakage protection , direct with long terminal shield in 600 + 300 mm Wide floor-standing enclosure + duct (cable coming

Informacije dane u ovoj dokumentaciji sadrže opće opise i/ili tehničke karakteristike o performansama ovdje sadržanih proizvoda.
Ova dokumentacija nije namijenjena kao zamjena za niti bi se trebala koristiti za određivanje prikladnosti ili pouzdanosti predmetnih proizvoda za konkretne korisničke primjene.
Svaki takav korisnik ili integrator dužan je provesti odgovarajuću i potpunu analizu rizika, procjenu i ispitivanje proizvoda u odnosu na odgovarajuću specifičnu primjenu ili uporabu istog.
Niti društvo Schneider Electric Industries SAS niti bilo koje od njegovih povezanih poduzeća ili podružnica neće preuzeti obvezu ili snositi odgovornost za pogrešnu upotrebu ovdje sadržanih informacija.

enclosure)
 5 module(s) : NSX250 without earth leakage protection , connection block in 600 mm Wide floor-standing enclosure (cable coming from top or bottom of enclosure)
 5 module(s) : NSX250 without earth leakage protection , connection block in 600 mm Wide wall-mounted enclosure (cable coming from top or bottom of enclosure)
 4 module(s) : NSX250 without earth leakage protection , direct with long terminal shield in 600 + 300 mm Wide floor-standing enclosure + duct (cable coming from top or bottom of enclosure)
 4 module(s) : NSX250 without earth leakage protection , direct with long terminal shield in 600 + 300 mm Wide wall-mounted enclosure + duct (cable coming from top or bottom of enclosure)
 5 module(s) : NSX250 without earth leakage protection , direct with long terminal shield in 600 mm Wide floor-standing enclosure (cable coming from top or bottom of enclosure)
 5 module(s) : NSX250 without earth leakage protection , direct with long terminal shield in 600 mm Wide wall-mounted enclosure (cable coming from top or bottom of enclosure)
 5 module(s) : NSX250 without earth leakage protection , connection block in 600 + 300 mm Wide floor-standing enclosure + duct (cable coming from top or bottom of enclosure)
 5 module(s) : NSX250 without earth leakage protection , connection block in 600 + 300 mm Wide wall-mounted enclosure + duct (cable coming from top or bottom of enclosure)
 5 module(s) : NSX250 without earth leakage protection , connection block in 850 mm Wide floor-standing enclosure (cable coming from top or bottom of enclosure)
 4 module(s) : NSX250 without earth leakage protection , direct with long terminal shield in 850 mm Wide floor-standing enclosure (cable coming from top or bottom of enclosure)
 6 module(s) : NSX250 without earth leakage protection , connection block in 600 mm Wide Pack enclosure (cable coming from top or bottom of enclosure)
 6 module(s) : NSX250 without earth leakage protection , direct with long terminal shield in 600 mm Wide Pack enclosure (cable coming from top or bottom of enclosure)

Condition of use	Need additional plate (2M high) when installation of device is in horizontal
Height	200 mm
Width	600 mm
Product weight	1.16 kg
Surface finish	Matt Smooth
Protective treatment	Electrophoresis treatment and hot-polymerised polyester epoxy powder
Colour	White RAL 9001

Okolina

standards	IEC 61439-2
product certifications	ASEFA

Offer Sustainability

Green Premium product	Green Premium product
Compliant - since 0807 - Schneider Electric declaration of conformity	Compliant - since 0807 - Schneider Electric declaration of conformity
Reference not containing SVHC above the threshold	Reference not containing SVHC above the threshold
Available	Available
Need no specific recycling operations	Need no specific recycling operations

Contractual warranty

Warranty period	18 months
-----------------	-----------