



### Glavno

Range	Prisma
Range compatibility	Prisma G
Product or component type	Mounting plate
Accessory / separate part category	Installation accessory
Installed device	<p>Easypact: fixed EZC400 - control: toggle - horizontal installation</p> <p>Easypact: fixed CVS400 without earth leakage protection - control: toggle - horizontal installation</p> <p>Easypact: fixed CVS630 without earth leakage protection - control: toggle - horizontal installation</p> <p>Compact: fixed INS320...400 - control: direct front rotary handle - horizontal installation</p> <p>Compact: fixed INS500...630 - control: direct front rotary handle - horizontal installation</p> <p>Compact: fixed INV320...400 - control: direct front rotary handle - horizontal installation</p> <p>Compact: fixed INV500...630 - control: direct front rotary handle - horizontal installation</p> <p>Compact: fixed NSX400 without earth leakage protection - control: toggle - horizontal installation</p> <p>Compact: fixed NSX630 without earth leakage protection - control: toggle - horizontal installation</p> <p>Easypact: fixed EZC630 - control: toggle - horizontal installation</p>
Poles description	<p>1 x 3P: fixed: NSX400 horizontal installation</p> <p>1 x 3P: fixed: NSX630 horizontal installation</p> <p>1 x 3P: fixed: EZC400 horizontal installation</p> <p>1 x 3P: fixed: EZC630 horizontal installation</p> <p>1 x 3P: fixed: CVS400 horizontal installation</p> <p>1 x 3P: fixed: CVS630 horizontal installation</p> <p>1 x 3P: fixed: INS320...400 horizontal installation</p> <p>1 x 3P: fixed: INS500...630 horizontal installation</p> <p>1 x 3P: fixed: INV320...400 horizontal installation</p> <p>1 x 3P: fixed: INV500...630 horizontal installation</p> <p>1 x 4P: fixed: NSX400 horizontal installation</p> <p>1 x 4P: fixed: NSX630 horizontal installation</p> <p>1 x 4P: fixed: EZC400 horizontal installation</p> <p>1 x 4P: fixed: EZC630 horizontal installation</p> <p>1 x 4P: fixed: CVS400 horizontal installation</p> <p>1 x 4P: fixed: CVS630 horizontal installation</p> <p>1 x 4P: fixed: INS320...400 horizontal installation</p> <p>1 x 4P: fixed: INS500...630 horizontal installation</p> <p>1 x 4P: fixed: INV320...400 horizontal installation</p> <p>1 x 4P: fixed: INV500...630 horizontal installation</p>

### Komplementarno

Enclosure/cubicle description	<p>Floor-standing enclosure - width 850 mm</p> <p>Floor-standing enclosure + duct - width 600 + 300 mm</p> <p>Wall-mounted enclosure + duct - width 600 + 300 mm</p>
Number of vertical modules [50 mm]	<p>9 module(s) : CVS400 without earth leakage protection , direct with long terminal shield in 600 + 300 mm Wide floor-standing enclosure + duct (cable coming from top of enclosure)</p> <p>9 module(s) : CVS400 without earth leakage protection , direct with long terminal shield in 600 + 300 mm Wide wall-mounted enclosure + duct (cable coming from top of enclosure)</p> <p>6 module(s) : CVS400 without earth leakage protection , direct with long terminal shield in 600 + 300 mm Wide floor-standing enclosure + duct (cable coming from bottom of enclosure)</p> <p>6 module(s) : CVS400 without earth leakage protection , direct with long terminal</p>



9 module(s) : INV500...630, direct with long terminal shield in 600 + 300 mm Wide wall-mounted enclosure + duct (cable coming from top of enclosure)

6 module(s) : INV500...630, direct with long terminal shield in 600 + 300 mm Wide floor-standing enclosure + duct (cable coming from bottom of enclosure)

6 module(s) : INV500...630, direct with long terminal shield in 600 + 300 mm Wide wall-mounted enclosure + duct (cable coming from bottom of enclosure)

9 module(s) : INV500...630, direct with long terminal shield in 850 mm Wide floor-standing enclosure (cable coming from top of enclosure)

6 module(s) : INV500...630, direct with long terminal shield in 850 mm Wide floor-standing enclosure (cable coming from bottom of enclosure)

9 module(s) : NSX400 without earth leakage protection , connection block in 850 mm Wide floor-standing enclosure (cable coming from top of enclosure)

6 module(s) : NSX400 without earth leakage protection , connection block in 850 mm Wide floor-standing enclosure (cable coming from bottom of enclosure)

9 module(s) : NSX400 without earth leakage protection , connection block in 600 + 300 mm Wide floor-standing enclosure + duct (cable coming from top of enclosure)

9 module(s) : NSX400 without earth leakage protection , connection block in 600 + 300 mm Wide wall-mounted enclosure + duct (cable coming from top of enclosure)

6 module(s) : NSX400 without earth leakage protection , connection block in 600 + 300 mm Wide floor-standing enclosure + duct (cable coming from bottom of enclosure)

6 module(s) : NSX400 without earth leakage protection , connection block in 600 + 300 mm Wide wall-mounted enclosure + duct (cable coming from bottom of enclosure)

9 module(s) : NSX400 without earth leakage protection , direct with long terminal shield in 600 + 300 mm Wide floor-standing enclosure + duct (cable coming from top of enclosure)

9 module(s) : NSX400 without earth leakage protection , direct with long terminal shield in 600 + 300 mm Wide wall-mounted enclosure + duct (cable coming from top of enclosure)

6 module(s) : NSX400 without earth leakage protection , direct with long terminal shield in 600 + 300 mm Wide floor-standing enclosure + duct (cable coming from bottom of enclosure)

6 module(s) : NSX400 without earth leakage protection , direct with long terminal shield in 600 + 300 mm Wide wall-mounted enclosure + duct (cable coming from bottom of enclosure)

9 module(s) : NSX400 without earth leakage protection , direct with long terminal shield in 850 mm Wide floor-standing enclosure (cable coming from top of enclosure)

6 module(s) : NSX400 without earth leakage protection , direct with long terminal shield in 850 mm Wide floor-standing enclosure (cable coming from bottom of enclosure)

9 module(s) : NSX630 without earth leakage protection , connection block in 850 mm Wide floor-standing enclosure (cable coming from top of enclosure)

6 module(s) : NSX630 without earth leakage protection , connection block in 850 mm Wide floor-standing enclosure (cable coming from bottom of enclosure)

9 module(s) : NSX630 without earth leakage protection , connection block in 600 + 300 mm Wide floor-standing enclosure + duct (cable coming from top of enclosure)

9 module(s) : NSX630 without earth leakage protection , connection block in 600 + 300 mm Wide wall-mounted enclosure + duct (cable coming from top of enclosure)

6 module(s) : NSX630 without earth leakage protection , connection block in 600 + 300 mm Wide floor-standing enclosure + duct (cable coming from bottom of enclosure)

6 module(s) : NSX630 without earth leakage protection , connection block in 600 + 300 mm Wide wall-mounted enclosure + duct (cable coming from bottom of enclosure)

9 module(s) : NSX630 without earth leakage protection , direct with long terminal shield in 600 + 300 mm Wide floor-standing enclosure + duct (cable coming from top of enclosure)

9 module(s) : NSX630 without earth leakage protection , direct with long terminal shield in 600 + 300 mm Wide wall-mounted enclosure + duct (cable coming from top of enclosure)

6 module(s) : NSX630 without earth leakage protection , direct with long terminal shield in 600 + 300 mm Wide floor-standing enclosure + duct (cable coming from bottom of enclosure)

6 module(s) : NSX630 without earth leakage protection , direct with long terminal shield in 600 + 300 mm Wide wall-mounted enclosure + duct (cable coming from bottom of enclosure)

9 module(s) : NSX630 without earth leakage protection , direct with long terminal shield in 850 mm Wide floor-standing enclosure (cable coming from top of enclosure)

6 module(s) : NSX630 without earth leakage protection , direct with long terminal shield in 850 mm Wide floor-standing enclosure (cable coming from bottom of enclosure)

Condition of use	Need additional plate (2M high) when installation of device is in horizontal
Height	250 mm
Width	600 mm
Product weight	2.24 kg

Surface finish	Matt Smooth
Protective treatment	Electrophoresis treatment and hot-polymerised polyester epoxy powder
Colour	White RAL 9001

### Okolina

standards	IEC 61439-2
product certifications	ASEFA

### Offer Sustainability

Green Premium product	Green Premium product
Compliant - since 0807 - Schneider Electric declaration of conformity	Compliant - since 0807 - Schneider Electric declaration of conformity
Reference not containing SVHC above the threshold	Reference not containing SVHC above the threshold
Available	Available
Need no specific recycling operations	Need no specific recycling operations

### Contractual warranty

Warranty period	18 months
-----------------	-----------