



Main

Range	Prisma
Range compatibility	Pack 160 Prisma G
IP degree of protection	IP30
Product or component type	Incoming kit
Accessory / separate part category	Installation accessory
Type of front plate	Cut-out
Installed device	Resi9 by screws DB 90 toggle - vertical relay
Poles description	1 x 1P + N mounting plate DB 90 vertical

Complementary

Enclosure/cubicle description	Floor-standing enclosure 600 mm Wall-mounted enclosure 600 mm Pack enclosure 555 mm
Number of vertical modules [50 mm]	6
Standards	IEC 61439-1 IEC 61439-2
Product certifications	ASEFA
Quantity per set	Set of 1
Maksimalna visina	300 mm
Neto težina	4,18 kg
Material	Steel
Surface finish	Smooth Matt
Protective treatment	Electrophoresis treatment and hot-polymerised polyester epoxy powder
Colour	Bijelo RAL 9001)

Environment

IK degree of protection	IK07 EN/IEC 62262
Ambient air temperature for operation	40 °C

Broj pakirnih jedinica

Vrsta pakirne jedinice Paketa 1	PCE
Vrsta pakirne jedinice Paketa 2	P12

Offer Sustainability

Status održive ponude	Proizvod Green Premium
REACH, bez SVHC	Da
Direktiva EU RoHS	Proaktivna sukladnost (proizvod izvan zakonskog okvira direktive EU RoHS) Izjava EU RoHS
Bez otrovnih teških metala	Da
Bez žive	Da

Informacije o RoHS izuzeću	Da
Propis RoHS za Kinu	Izjava RoHS Za Kinu
Izjava o očuvanju okoliša	Ekološki Profil Proizvoda

Contractual warranty

Jamstvo	18 months
---------	-----------