



### Main

Range	Prisma
Range compatibility	Prisma G duct
IP degree of protection	IP30
Product or component type	Metering panel kit
Accessory / separate part category	Installation accessory
Type of front plate	Cut-out
Installed device	Resi9 by screws DB 90 toggle - vertical Power meters kilowatt-hour meters - vertical
Poles description	1 x 1P + N mounting plate DB 90 vertical 1 x 3P + N mounting plate kilowatt-hour meters vertical

### Complementary

Enclosure/cubicle description	Floor-standing duct 300 mm Wall-mounted duct 300 mm
Number of vertical modules [50 mm]	13
Standards	IEC 61439-2 IEC 61439-1
Product certifications	ASEFA
Quantity per set	Set of 1
Maksimalna visina	650 mm
Maksimalna širina	300 mm
Neto težina	4,92 kg
Material	Steel
Surface finish	Matt Smooth
Protective treatment	Electrophoresis treatment and hot-polymerised polyester epoxy powder
Colour	Bijelo RAL 9001)

### Environment

IK degree of protection	IK07 EN/IEC 62262
Ambient air temperature for operation	40 °C

### Broj pakirnih jedinica

Vrsta pakirne jedinice Paketa 1	PCE
Vrsta pakirne jedinice Paketa 2	P12

## Offer Sustainability

Status održive ponude	Proizvod Green Premium
Uredba REACh	<a href="#">Izjava REACh</a>
REACh, bez SVHC	Da
Direktiva EU RoHS	Proaktivna sukladnost (proizvod izvan zakonskog okvira direktive EU RoHS) <a href="#">Izjava EU RoHS</a>
Bez otrovnih teških metala	Da
Bez žive	Da
Informacije o RoHS izuzeću	<a href="#">Da</a>
Propis RoHS za Kinu	<a href="#">Izjava RoHS Za Kinu</a>
Izjava o očuvanju okoliša	<a href="#">Ekološki Profil Proizvoda</a>

## Contractual warranty

Jamstvo	18 months
---------	-----------