

## 04014

Linery FM 3P+N distribucijski blok 200 A– 24 modula 54 otvora za brzo spajanje



### Glavno

Range	Linery
Product name	Linery FM
IP degree of protection	IPxx B
Product or component type	Device feeder
Product compatibility	Spacial enclosures

### Komplementarno

Mounting support	DIN rail Plain backplate Slotted backplate
Installed device	Modular device
Poles description	3P + N
[Ue] rated operational voltage	690 V AC
[Ui] rated insulation voltage	750 V AC 50/60 Hz
[Uimp] rated impulse withstand voltage	8 kV
[Ie] rated operational current	200 A
[Ipk] rated peak withstand current	20 kA
I <sup>2</sup> t on activation	6700000 A <sup>2</sup> .s
Connections - terminals	Supply: crimped lug 50 mm <sup>2</sup> Supply: flexible bars, 20 x 3 mm Distribution: quick-connect terminal strips (phase) , 12 x 4...10 mm <sup>2</sup> (flexible) Distribution: quick-connect terminal strips (phase) , 12 x 4...10 mm <sup>2</sup> (rigid) Distribution: quick-connect terminal strips (neutral) , 18 x 4...10 mm <sup>2</sup> (flexible) Distribution: quick-connect terminal strips (neutral) , 18 x 4...10 mm <sup>2</sup> (rigid)
Total number of 18 mm modules	24
Product weight	1.6 kg
Colour	Anthracite grey RAL 7016

### Okolina

standards	IEC 61439-1 inside Prisma IEC 61439-2 inside Prisma IEC 60947-7-1
product certifications	ASEFA

### Offer Sustainability

Green Premium product	Green Premium product
Compliant - since 0813 - Schneider Electric declaration of conformity	Compliant - since 0813 - Schneider Electric declaration of conformity
Reference not containing SVHC above the threshold	Reference not containing SVHC above the threshold
Available	Available
Need no specific recycling operations	Need no specific recycling operations

### Contractual warranty

