

Podatkovni list proizvoda

Karakteristike

04041

Lineryg DX 4P distrib. blok 63 A–4 modula–donja strana s 24 otvora za brzo spaj.



Glavno

Range	Lineryg
Product name	Lineryg DX
IP degree of protection	IPxx B
Product or component type	Distribution block
Product compatibility	Spacial enclosures

Komplementarno

Location of connection	Bottom
Mounting support	DIN rail
Poles description	4P
[Ue] rated operational voltage	440 V AC
[Ui] rated insulation voltage	500 V AC
[Uimp] rated impulse withstand voltage	8 kV
[Ie] rated operational current	63 A at 40 °C
Connections - terminals	Supply: tunnel type terminal 16 mm ² (flexible) Supply: tunnel type terminal 25 mm ² (rigid) Distribution: spring terminal (phase) , 12 x 2.5...6 mm ² (flexible) Distribution: spring terminal (phase) , 12 x 2.5...6 mm ² (rigid) Distribution: spring terminal (neutral) , 12 x 2.5...6 mm ² (flexible) Distribution: spring terminal (neutral) , 12 x 2.5...6 mm ² (rigid)
Total number of 18 mm modules	4
Product weight	0.29 kg

Okolina

pollution degree	3
resistance to incandescent wire	960 °C conforming to IEC 60695-2-11
standards	IEC 61439-2 IEC 60947-7-1 IEC 61439-1
product certifications	ASEFA

Offer Sustainability

Not Green Premium product	Not Green Premium product
Compliant - since 1001 - Schneider Electric declaration of conformity	Compliant - since 1001 - Schneider Electric declaration of conformity

Contractual warranty

Warranty period	18 months
-----------------	-----------

Informacije dane u ovoj dokumentaciji sadrže opće opise i/ili tehničke karakteristike o performansama ovdje sadržanih proizvoda. Ova dokumentacija nije namijenjena kao zamjena za niti bi se trebala koristiti za određivanje prikladnosti ili pouzdanosti predmetnih proizvoda za konkretne korisničke primjene. Svaki takav korisnik ili integrator dužan je provesti odgovarajuću i potpunu analizu rizika, procjenu i ispitivanje proizvoda u odnosu na odgovarajuću specifičnu primjenu ili uporabu istog. Niti društvo Schneider Electric Industries SAS niti bilo koje od njegovih povezanih poduzeća ili podružnica neće preuzeti obvezu ili snositi odgovornost za pogrešnu upotrebu ovdje sadržanih informacija.