



Glavno

Range	Prisma
Product name	Pack 160
IP degree of protection	IP31 with door and canopy IP43 with door, canopy and IP43 gasket IP30 with door IP30 without door
Product or component type	Enclosure
Enclosure type	Modular enclosure
Enclosure mounting	Surface Flush with kit
Type of front cover	Modular
Number of vertical modules [50 mm]	18
Number of 18 mm modules per row	24
Provided equipment	Enclosure (x1) Earthing kit (x1) Front plate (x6) Modular rail (x6)

Komplementarno

Enclosure/cubicle description	Pack enclosure - width 555 mm
[Ui] rated insulation voltage	750 V on main rear busbars conforming to IEC 61439-2
[In] rated current	160 Aat 40 °C conforming to IEC 61439-2
[Icw] rated short-time withstand current	25 kA (1 s) conforming to IEC 61439-2
[Ipk] rated peak withstand current	53 kA conforming to IEC 61439-2
Network frequency	50/60 Hz
Number of horizontal rows	6
Enclosure material	Enclosure: treated sheet steel
Quantity per set	Set of 1
Height	1080 mm
Width	555 mm
Depth	157 mm
Product weight	16.06 kg
Surface finish	Matt Smooth
Colour	White RAL 9001

Okolina

IK degree of protection	IK08 with door IK07 without door conforming to EN/IEC 62262
protective treatment	Electrophoresis treatment and hot-polymerised polyester epoxy powder
standards	IEC 62208 IEC 61439-2 IEC 61439-1 IEC 61439-3

Offer Sustainability

Informacije dane u ovoj dokumentaciji sadrže opće opise i/ili tehničke karakteristike o performansama ovdje sadržanih proizvoda. Ova dokumentacija nije namijenjena kao zamjena za niti bi se trebala koristiti za određivanje prikladnosti ili pouzdanosti predmetnih proizvoda za konkretne korisničke primjene. Svaki takav korisnik ili integrator dužan je provesti odgovarajuću i potpunu analizu rizika, procjenu i ispitivanje proizvoda u odnosu na odgovarajuću specifičnu primjenu ili uporabu istog. Niti društvo Schneider Electric Industries SAS niti bilo koje od njegovih povezanih poduzeća ili podružnica neće preuzeti obvezu ili snositi odgovornost za pogrešnu upotrebu ovdje sadržanih informacija.

Green Premium product	Green Premium product
Compliant - since 1809 - Schneider Electric declaration of conformity	Compliant - since 1809 - Schneider Electric declaration of conformity
Reference not containing SVHC above the threshold	Reference not containing SVHC above the threshold
Available	Available
Need no specific recycling operations	Need no specific recycling operations

Contractual warranty

Warranty period	18 months
-----------------	-----------