



Glavno

Range	Prisma
Product name	Pack 160
IP degree of protection	IP30
Product or component type	Door
Enclosure mounting	Surface Flush with kit
Type of front cover	Plain
Provided equipment	Door Handle Keylock (key 405) Other keylock and insert (to be ordered separately) Hinge (x2)

Komplementarno

Door opening side	Reversible
Number of locks	1
Opening size	130 °
Number of 18 mm modules per row	24
Total number of 18 mm modules	72
Enclosure/cubicle description	Pack enclosure - width 555 mm Extension enclosure - width 555 mm
Number of vertical modules [50 mm]	12
Number of horizontal rows	3
Enclosure material	Treated sheet steel
Quantity per set	Set of 1
Height	630 mm
Width	550 mm
Depth	22 mm
Product weight	3.8 kg
Surface finish	Matt Smooth
Colour	White RAL 9001

Okolina

IK degree of protection standards	IK08 conforming to EN/IEC 62262 IEC 61439-2 IEC 61439-1
protective treatment	Electrophoresis treatment and hot-polymerised polyester epoxy powder

Offer Sustainability

Green Premium product	Green Premium product
Compliant - since 0823 - Schneider Electric declaration of conformity	Compliant - since 0823 - Schneider Electric declaration of conformity
Reference not containing SVHC above the threshold	Reference not containing SVHC above the threshold
Available	Available
Need no specific recycling operations	Need no specific recycling operations

Informacije dane u ovoj dokumentaciji sadrže opće opise i/ili tehničke karakteristike o performansama ovdje sadržanih proizvoda. Ova dokumentacija nije namijenjena kao zamjena za niti bi se trebala koristiti za određivanje prikladnosti ili pouzdanosti predmetnih proizvoda za konkretne korisničke primjene. Svaki takav korisnik ili integrator dužan je provesti odgovarajuću i potpunu analizu rizika, procjenu i ispitivanje proizvoda u odnosu na odgovarajuću specifičnu primjenu ili uporabu istog. Niti društvo Schneider Electric Industries SAS niti bilo koje od njegovih povezanih poduzeća ili podružnica neće preuzeti obvezu ili snositi odgovornost za pogrešnu upotrebu ovdje sadržanih informacija.

Contractual warranty

Warranty period	18 months
-----------------	-----------
