



### Glavno

Range	Prisma
Product name	Prisma G
IP degree of protection	IP43 with door, canopy and IP43 gasket IP40 with door IP30 without door IP41 with door and canopy
Product or component type	Enclosure
Enclosure type	Functional enclosure delivered in kit form
Device application	Low voltage electrical distribution
Enclosure mounting	Surface
Type of front cover	Without (to be ordered separately)
Number of vertical modules [50 mm]	30
Number of 18 mm modules per row	24

### Komplementarno

Enclosure/cubicle description	Floor-standing enclosure - width 600 mm
[U] rated insulation voltage	1000 V on main rear busbars conforming to IEC 61439-2
[In] rated current	630 Aat 40 °C conforming to IEC 61439-2
[Icw] rated short-time withstand current	25 kA (1 s) conforming to IEC 61439-2
[Ipk] rated peak withstand current	53 kA conforming to IEC 61439-2
Network frequency	50/60 Hz
Enclosure material	Enclosure: treated sheet steel
Additional information	Can be combined side by side and one on top of another
Quantity per set	Set of 1
Height	1680 mm, with plinth
Width	600 mm
Depth	205 mm
Product weight	25.1 kg
Surface finish	Matt Smooth
Colour	White RAL 9001

### Okolina

IK degree of protection	IK08 with door IK07 without door conforming to EN/IEC 62262
protective treatment	Electrophoresis treatment and hot-polymerised polyester epoxy powder
standards	IEC 62208 IEC 61439-2 IEC 61439-1
mechanical robustness	Seismic tests: 2.5G conforming to IEC 60068-2-57

### Offer Sustainability

Green Premium product	Green Premium product
Compliant - since 1809 - Schneider Electric declaration of conformity	Compliant - since 1809 - Schneider Electric declaration of conformity
Reference not containing SVHC above the threshold	Reference not containing SVHC above the threshold

---

Available	Available
Need no specific recycling operations	Need no specific recycling operations

---

### Contractual warranty

---

Warranty period	18 months
-----------------	-----------

---