



## Glavno

|                                     |                            |
|-------------------------------------|----------------------------|
| Range                               | Kaedra                     |
| Product or component type           | Weatherproof enclosure     |
| Enclosure type                      | Enclosure for power outlet |
| Accessories included with enclosure | 1 terminal block 4 holes   |

## Komplementarno

|                                 |   |
|---------------------------------|---|
| Enclosure mounting              | Surface   |
| Number of 18 mm modules per row | 4   |
| Total number of 18 mm modules   | 4   |
| Number of horizontal rows       | 1   |
| Electrical insulation class     | Class II<br>Double insulation                                   |
| Number of openings of interface | 1   |
| Provided equipment              | 1 terminal block 4 holes  |
| Type of front cover             | Transparent   |
| Power dissipation in W          | 10 W  |
| [In] rated current              | 63 A  |
| Type of rail                    | DIN   |
| Number of pre-cutouts PG ISO    | 1   |
| Number of terminal blocks       | 1 with 4 outgoers   |
| Distribution block outgoers     | 2 x 10 mm <sup>2</sup><br>2 x 16 mm <sup>2</sup>                |
| Locking options description     | Optional keylock  |
| Enclosure material              | Housing: self-extinguishing polymer                             |
| Product weight                  | 0.425 kg  |
| Base dimension                  | 65 x 85 mm  |
| Width                           | 98 mm   |
| Height                          | 248 mm  |
| Depth                           | 98 mm   |
| Colour                          | Door : transparent green<br>Enclosure : light grey ( RAL 7035 ) |

## Okolina

|                              |  |
|------------------------------|--|
| standards                    | EN 50262<br>EN 62262<br>IEC 60439-3<br>IEC 60529<br>IEC 60695-2-1<br>IEC 670                                   |
| fire resistance              | 650 °C conforming to IEC 60695-2-1   |
| IP degree of protection      | IP65 conforming to IEC 60529   |
| IK degree of protection      | IK09 conforming to EN 50102  |
| environmental characteristic | UV resistant class 3 conforming to ISO 4582 2010<br>Ultraviolet degradation test conforming to ISO 4892-2 2013 |

Informacije dane u ovoj dokumentaciji sadrže opće opise i/ili tehničke karakteristike o performansama ovdje sadržanih proizvoda. Ova dokumentacija nije namijenjena kao zamjena za niti bi se trebala koristiti za određivanje prikladnosti ili pouzdanosti predmetnih proizvoda za konkretne korisničke primjene. Svaki takav korisnik ili integrator dužan je provesti odgovarajuću i poplunu analizu rizika, procjenu i ispitivanje proizvoda u odnosu na odgovarajuću specifičnu primjenu ili uporabu istog. Niti društvo Schneider Electric, Industries SAS niti bilo koje od njegovih povezanih poduzeća ili podružnica neće preuzeti obvezu ili snositi odgovornost za pogrešnu upotrebu ovdje sadržanih informacija.

|                                       |             |
|---------------------------------------|-------------|
| overvoltage category                  | II          |
| ambient air temperature for operation | -25...40 °C |

---

### Contractual warranty

|                 |           |
|-----------------|-----------|
| Warranty period | 18 months |
|-----------------|-----------|