



### Glavno

Range	Acti 9
Product name	Acti 9 IH
Device short name	IH
Product or component type	Mechanical time switch
Number of channels	2
Function available	Manual time changeover

### Komplementarno

Device application	Building
Load type	1 parallel-corrected fluorescent tube, balast : conventional, ( 58 W ) 10 non-corrected fluorescent tube, balast : conventional, ( 58 W ) 10 serial-corrected fluorescent tube, balast : conventional, ( 58 W ) 15 non-corrected fluorescent tube, balast : conventional, ( 40 W ) 15 serial-corrected fluorescent tube, balast : conventional, ( 40 W ) 2 parallel-corrected fluorescent tube, balast : conventional, ( 40 W ) 230 V AC halogen lamp, ( 1100 W ) 230 V AC incandescent lamp, ( 1100 W ) 3 dual mounted fluorescent tube, balast : conventional, ( 2 x 100 W ) 5 dual mounted fluorescent tube, balast : conventional, ( 2 x 58 W ) 6 non-corrected fluorescent tube, balast : conventional, ( 100 W ) 6 serial-corrected fluorescent tube, balast : conventional, ( 100 W )
Cycle duration	24 h
Measurement accuracy	+/- 1 s/day
Maximum number of switchings	24 on - 24 off
Minimum interval duration	30 min
Type of setting	Manual time changeover
Measurement accuracy	+/- 1 s/day 20 °C
Power consumption in VA	2.5 VA
Maximum switching current	16 A - 250 V AC pf = 1 4 A - 250 V AC pf = 0.6
[Ue] rated operational voltage	( - 15...10 % ) 230 V AC 50/60 Hz
Battery life	6 yr
Backup time	150 h time and program saving
Mounting support	DIN rail
9 mm pitches	6
Colour tint	White (RAL 9003)
Connections - terminals	Screw terminals
IP degree of protection	IP20 B
Width	54 mm
Height	82 mm
Depth	66 mm
Product weight	0.216 kg

### Okolina

ambient air temperature for operation	-20...55 °C
IP degree of protection	Terminals : IP20 B

Informacije dane u ovoj dokumentaciji sadrže opće opise i/ili tehničke karakteristike o performansama ovdje sadržanih proizvoda.  
Ova dokumentacija nije namijenjena kao zamjena za niti bi se trebala koristiti za određivanje prikladnosti ili pouzdanosti predmetnih proizvoda za konkretne korisničke primjene.  
Svaki takav korisnik ili integrator dužan je provesti odgovarajuću i potpunu analizu rizika, procjenu i ispitivanje proizvoda u odnosu na odgovarajuću specifičnu primjenu ili uporabu istog.  
Niti društvo Schneider Electric, Industries SAS niti bilo koje od njegovih povezanih poduzeća ili podružnica neće preuzeti obvezu ili snositi odgovornost za pogrešnu upotrebu ovdje sadržanih informacija.

## Offer Sustainability

3303430153375	3303430153375
Compliant - since 0619 - Schneider Electric declaration of conformity	Compliant - since 0619 - Schneider Electric declaration of conformity
Reference contains SVHC above the threshold - go to CaP for more details	Reference contains SVHC above the threshold
3303430153375	3303430153375
3303430153375	3303430153375

## Contractual warranty

Warranty period	18 months
-----------------	-----------