



Glavno

Range	Acti 9
Product name	Acti 9 IC
Product or component type	Twilight switch
Device short name	IC100
Product compatibility	Mechanical compatibility with electrical distribution comb busbars
Provided equipment	Wall-mounted cell

Komplementarno

Device application	Building
Number of channels	1
Load type	(400 VA) Balast : conventional, (1500 VA) Balast : conventional, (2300 VA) Balast : conventional, (2300 VA) Balast : conventional, (2300 VA) (1000 VA) (1000 VA) Balast : conventional, (400 VA) (2300 W) (2300 W) Balast : electronic, (300 VA) Balast : electronic, (7 x 15 W) Balast : electronic, (7 x 20 W) Balast : electronic, (7 x 23 W) Balast : electronic, (9 x 7 W) Balast : electronic, (7 x 11 W)
Power consumption in VA	6 VA
Maximum switching current	10 A - 250 V AC pf = 0.6 16 A - 250 V AC pf = 1
[Ue] rated operational voltage	230 V (+10 % -15 %) AC 50/60 Hz
Opening distance	< 3 mm
Status LED	Green LED : threshold reached Red LED : brightness less than the threshold
Time delay	20 s (on closing) 80 s (on breaking contact)
Mounting support	DIN rail
9 mm pitches	2
Light intensity adjustment	2...100 lux
Connections - terminals	X 1 screw terminals : 6 mm ²
Electrical insulation class	Class II
Height	83 mm
Width	18 mm
Depth	68 mm
Product weight	173 g
Control type	By brightness detection

Okolina

standards	EN 60529
-----------	----------

Informacije dane u ovoj dokumentaciji sadrže opće opise i/ili tehničke karakteristike o performansama ovdje sadržanih proizvoda. Ova dokumentacija nije namijenjena kao zamjena za niti bi se trebala koristiti za određivanje prikladnosti ili pouzdanosti predmetnih proizvoda za konkretne korisničke primjene. Svaki takav korisnik ili integrator dužan je provesti odgovarajuću i potpunu analizu rizika, procjenu i ispitivanje proizvoda u odnosu na odgovarajuću specifičnu primjenu ili uporabu istog. Niti društvo Schneider Electric Industries SAS niti bilo koje od njegovih povezanih poduzeća ili podružnica neće preuzeti obvezu ili snositi odgovornost za pogrešnu upotrebu ovdje sadržanih informacija.

	EN 60669
ambient air temperature for operation	-20...50 °C
IP degree of protection	IP20 B

Offer Sustainability

Green Premium product	Green Premium product
Compliant - since 0625 - Schneider Electric declaration of conformity	Compliant - since 0625 - Schneider Electric declaration of conformity
Reference not containing SVHC above the threshold	Reference not containing SVHC above the threshold
Available	Available

Contractual warranty

Warranty period	18 months
-----------------	-----------