

15483

Acti9-IC2000P+-prog. večernji prekidač s  
funk.vrem.prebacivanja-2...2100 luksa



### Glavno

Range	Acti 9
Product name	Acti 9 IC
Product or component type	Programmable twilight switch with time switch function
Device short name	IC2000P+
Device application	Building
Provided equipment	Wall-mounted cell
Load type	230 V AC halogen lamp, ( 2300 W ) 230 V AC incandescent lamp, ( 2600 W ) Non-corrected fluorescent tube, balast : conventional, ( 10 x 100 W ) Parallel-corrected fluorescent tube, balast : conventional, ( 10 x 36 W ) Serial-corrected fluorescent tube, balast : conventional, ( 10 x 100 W ) Parallel-corrected fluorescent tube, balast : conventional, ( 2 x 100 W ) Non-corrected fluorescent tube, balast : conventional, ( 20 x 58 W ) Serial-corrected fluorescent tube, balast : conventional, ( 20 x 58 W ) Non-corrected fluorescent tube, balast : conventional, ( 26 x 36 W ) Serial-corrected fluorescent tube, balast : conventional, ( 26 x 36 W ) Fluorescent tube, balast : electronic, ( 6 x 58 W ) Parallel-corrected fluorescent tube, balast : conventional, ( 6 x 58 W ) Fluocompact lamp, balast : electronic, ( 7 x 11 W ) Fluocompact lamp, balast : electronic, ( 7 x 15 W ) Fluocompact lamp, balast : electronic, ( 7 x 20 W ) Fluocompact lamp, balast : electronic, ( 9 x 7 W ) Fluorescent tube, balast : electronic, ( 9 x 36 W ) Dual mounted fluorescent tube, balast : conventional, ( 26 x 36 W ) Dual mounted fluorescent tube, balast : conventional, ( 20 x 58 W ) Dual mounted fluorescent tube, balast : conventional, ( 10 x 100 W ) Parallel-corrected mercury and sodium vapour lamps, ( 250 VA ) Dual mounted fluorescent tube, balast : electronic, ( 5 x ( 2 x 36 W ) ) Dual mounted fluorescent tube, balast : electronic, ( 3 x ( 2 x 58 W ) )
Battery type	Lithium
User language	Dutch English Finnish French German Italian Portuguese Spanish Swedish

### Komplementarno

Power consumption in VA	3 VA
[Ue] rated operational voltage	230 V ( +10 % -15 % ) AC 50/60 Hz

Informacije dane u ovoj dokumentaciji sadrže opće opise i/ili tehničke karakteristike o performansama ovdje sadržanih proizvoda. Ova dokumentacija nije namijenjena kao zamjena za niti bi se trebala koristiti za određivanje prikladnosti ili pouzdanosti predmetnih proizvoda za konkretne korisničke primjene. Svaki takav korisnik ili integrator dužan je provesti odgovarajuću i poplunu analizu rizika, procjenu i ispitivanje proizvoda u odnosu na odgovarajuću specifičnu primjenu ili uporabu istog. Niti društvo Schneider Electric, Industries SAS niti bilo koje od njegovih povezanih poduzeća ili podružnica neće preuzeti obvezu ili snositi odgovornost za pogrešnu upotrebu ovdje sadržanih informacija.

Maximum switching current	10 A - 250 V AC pf = 0.6 16 A - 250 V AC pf = 1
Electrical insulation class	Class II
Measurement accuracy	< +/- 1 s/day
Number of channels	1
9 mm pitches	5
Maximum number of switchings	42
Minimum interval duration	1 min
Function available	Automatic time changeover Coupling with time switch functions
Control type	By brightness detection
Display type	Backlit LCD
Time delay range	80 s (by default) 20...140 s (on closing) 20...140 s (on contact breaking)
Backup time	5...6 years time and program saving
Type of setting	Weekly programming
Light intensity adjustment	2...50 lux 350...2100 lux 60...300 lux
Connections - terminals	X 1 screw terminal: <= 6 mm <sup>2</sup>
Cable stiffness	Flexible Rigid
Mounting support	DIN rail
Height	83.5 mm
Width	45 mm
Depth	65 mm
Product weight	323 g

## Okolina

IP degree of protection	IP55 IP20 B
standards	EN 60529 EN 60730-1
ambient air temperature for operation	-20...50 °C

## Offer Sustainability

Green Premium product	Green Premium product
Compliant - since 0519 - Schneider Electric declaration of conformity	Compliant - since 0519 - Schneider Electric declaration of conformity
Reference not containing SVHC above the threshold	Reference not containing SVHC above the threshold
Available	Available

## Contractual warranty

Warranty period	18 months
-----------------	-----------