



Glavno

Product or component type	Cartridge
Device short name	C1 Neutral-350
Surge arrester type	Electrical distribution network

Komplementarno

Surge arrester class type	Type 1
Surge arrester technology	Spark gap
Earthing system	TN TT
[Ue] rated operational voltage	230 V AC 50 Hz
Nominal discharge current	20 kA
[Uc] maximum continuous operating voltage	350 V
[Up] voltage protection level	1.5 kV type 1
[If] follow current	0.1 kA
Mounting mode	Plug-in
Mounting support	Into SPD module
9 mm pitches	4
Height	50 mm
Width	36 mm
Depth	57 mm
Colour	Anthracite grey (RAL 7016)
Material	PBT (polybutylene terephthalate)
Response time	< 100 ns

Okolina

standards	EN 61643-11 IEC 61643-1
product certifications	KEMA-KEUR
IP degree of protection	Front face: IP20
relative humidity	5...90 %
operating altitude	0...2000 m
ambient air temperature for operation	-25...60 °C
ambient air temperature for storage	-40...80 °C

Offer Sustainability

Not Green Premium product	Not Green Premium product
Compliant - since 0902 - Schneider Electric declaration of conformity	Compliant - since 0902 - Schneider Electric declaration of conformity
Reference not containing SVHC above the threshold	Reference not containing SVHC above the threshold

Informacije dane u ovoj dokumentaciji sadrže opće opise i/ili tehničke karakteristike o performansama ovdje sadržanih proizvoda. Ova dokumentacija nije namijenjena kao zamjena za niti bi se trebala koristiti za određivanje prikladnosti ili pouzdanosti predmetnih proizvoda za konkretne korisničke primjene. Svaki takav korisnik ili integrator dužan je provesti odgovarajuću i potpunu analizu rizika, procjenu i ispitivanje specifičnu primjenu ili uporabu istog. Niti društvo Schneider Electric, Industries SAS niti bilo koje od njegovih povezanih poduzeća ili podružnica neće preuzeti obvezu ili snositi odgovornost za pogrešnu upotrebu ovdje sadržanih informacija.

Contractual warranty

Warranty period	18 months
-----------------	-----------
