



Glavno

Range	Acti 9
Product name	Acti 9 PRD1
Product or component type	Surge arrester with pluggable cartridge
Device short name	PRD1 35r
Device application	Distribution
Poles description	1P
Remote signalling	With
Signal contacts composition	1 SD (1 C/O)
Surge arrester type	Electrical distribution network
Earthing system	IT TN-C TN-S

Komplementarno

Surge arrester class type	Type 1
Surge arrester technology	Spark gap
[Ue] rated operational voltage	400/690 V AC(TN) 400 V AC(IT)
Nominal discharge current	Differential mode: 35 kA L/N Common mode: 35 kA L/PE
Maximum discharge current	Differential mode: 50 kA L/N
[Iimp] impulse current	Common mode: 35 kA L/PE 17.5 A.s Differential mode: 35 kA L/N
[Uc] maximum continuous operating voltage	Common mode: 440 V L/PE Differential mode: 440 V L/N
[Up] voltage protection level	2.5 kV type 1 common mode L/PE
[Ut] temporary overvoltage	Withstand: 580 V L/Nfor 5 s Withstand: 800 V N/PEfor 7200 s Safe failure mode: 1640 V L/Nfor 0.2 s
[If] follow current	50 kA differential mode L/N
Disconnecter device type	Associated circuit breaker NSX 160B 160 A - Icu 10 kA Associated circuit breaker NSX 160B 160 A - Icu 15 kA Associated circuit breaker NSX 160B 160 A - Icu 25 kA Associated circuit breaker NSX160F 160 A - Icu 36 kA Associated circuit breaker NSX160N 160 A - Icu 50 kA Associated fuse gG 400 A
Short-circuit withstand	50 kA
Short-circuit withstand	50 kA
Local signalling	Flag color: white/red
Signalling circuit voltage	1 A/250 V AC 1 A/30 V DC
Mounting mode	Clip-on
Mounting support	DIN rail
9 mm pitches	4
Height	99 mm
Width	36 mm
Depth	71 mm
Product weight	401 g
Colour	Anthracyte grey (RAL 7016)
Response time	<= 100 ns
Residual current	<= 0.005 mA

Informacije dane u ovoj dokumentaciji sadrže opće opise i/ili tehničke karakteristike o performansama ovdje sadržanih proizvoda. Ova dokumentacija nije namijenjena kao zamjena za niti bi se trebala koristiti za određivanje prikladnosti ili pouzdanosti predmetnih proizvoda za konkretne korisničke primjene. Svaki takav korisnik ili integrator dužan je provesti odgovarajuću i potpunu analizu rizika, procjenu i ispitivanje proizvoda u odnosu na odgovarajuću specifičnu primjenu ili uporabu istog. Niti društvo Schneider Electric, Industries SAS niti bilo koje od njegovih povezanih poduzeća ili podružnica neće preuzeti obvezu ili snositi odgovornost za pogrešnu upotrebu ovdje sadržanih informacija.

Connections - terminals	Tunnel type terminal, top or bottom 10...25 mm ² cable(s) flexible Tunnel type terminal, top or bottom 16...35 mm ² cable(s) rigid
Tightening torque	4.5 N.m

Okolina

standards	EN 61643-11: 2012 IEC 61643-11: 2011
product certifications	CE
quality labels	NF
IP degree of protection	On front face: IP40 conforming to IEC 60529 Built-in: IP20 conforming to IEC 60529
IK degree of protection	IK05 conforming to IEC 62262
relative humidity	5...95 %
operating altitude	2000 m
ambient air temperature for operation	-25...60 °C
ambient air temperature for storage	-40...85 °C

Offer Sustainability

Not Green Premium product	Not Green Premium product
Reference not containing SVHC above the threshold	Reference not containing SVHC above the threshold