



### Glavno

Range	Acti 9
Product name	Acti 9 RCCB-ID
Product or component type	Residual current circuit breaker (RCCB)
Device short name	RCCB-ID
Poles description	4P
Neutral position	Left
[In] rated current	125 A
Network type	AC
Earth-leakage sensitivity	500 mA
Earth-leakage protection time delay	Instantaneous
Earth-leakage protection class	Type B
Rated breaking and making capacity	Im 1250 A conforming to IEC 61008
Rated conditional short-circuit current	Inc 10 kA 125 A

### Komplementarno

Device location in system	Outgoer
Network frequency	50/60 Hz
[Ue] rated operational voltage	230/400 V
[Ui] rated insulation voltage	440 V AC 50 Hz conforming to IEC 61008-1
[Uimp] rated impulse withstand voltage	4 kV conforming to IEC 61008-1
Connection pitch	
9 mm pitches	8
Height	86 mm
Width	72 mm
Depth	76 mm
Product weight	450 g
Colour	Grey
Mechanical durability	5000 cycles
Electrical durability	2000 cycles
Connections - terminals	Tunnel type terminals 2 cable(s) 1.5...16 mm <sup>2</sup> flexible Tunnel type terminals 2 cable(s) 1.5...16 mm <sup>2</sup> flexible Tunnel type terminals 2 cable(s) 1.5...16 mm <sup>2</sup> rigid Tunnel type terminals 1 cable(s) 1.5...50 mm <sup>2</sup> rigid Tunnel type terminals 1 cable(s) 1.5...35 mm <sup>2</sup> flexible Tunnel type terminals 1 cable(s) 1.5...35 mm <sup>2</sup> flexible with ferrule Tunnel type terminals 2 cable(s) 1.5...16 mm <sup>2</sup> flexible with ferrule
Wire stripping length	11 mm
Tightening torque	3 N.m

### Okolina

standards	EN 61008 IEC 61008 VDE 0664
IP degree of protection	IP20 conforming to IEC 60529 IP40 in modular enclosure conforming to IEC 60529
tropicalisation	2
relative humidity	95 % ( 55 °C )

Informacije dane u ovoj dokumentaciji sadrže opće opise i/ili tehničke karakteristike o performansama ovdje sadržanih proizvoda. Ova dokumentacija nije namijenjena kao zamjena za niti bi se trebala koristiti za određivanje prikladnosti ili pouzdanosti predmetnih proizvoda za konkretne korisničke primjene. Svaki takav korisnik ili integrator dužan je provesti odgovarajuću i poplunu analizu rizika, procjenu i ispitivanje proizvoda u odnosu na odgovarajuću specifičnu primjenu ili uporabu istog. Niti društvo Schneider Electric Industries SAS niti bilo koje od njegovih povezanih poduzeća ili podružnica neće preuzeti obvezu ili snositi odgovornost za pogrešnu upotrebu ovdje sadržanih informacija.

---

ambient air temperature for operation -25...40 °C

---

ambient air temperature for storage -40...85 °C

---