



### Glavno

Range	Multi 9
Product or component type	OC contact
Device short name	OFSP
Signal contacts composition	1 C/O 1 NC
[In] rated current	3 A at 380...415 V AC - 50/60 Hz 6 A at 220...240 V AC - 50/60 Hz 1 A at 130 V DC 1.5 A at 60 V DC 2 A at 48 V DC 6 A at 24 V DC

### Komplementarno

Mounting mode	Fixed
Mounting support	DIN rail
Connections - terminals	Tunnel type terminal 2 cable(s) 1...1.5 mm <sup>2</sup> flexible Tunnel type terminal 2 cable(s) 1...1.5 mm <sup>2</sup> rigid
Tightening torque	0.8 N.m

### Okolina

standards	EN/IEC 60947-5-1
IP degree of protection	IP20 conforming to EN/IEC 60947-5-1
pollution degree	3 conforming to EN/IEC 60947-5-1
ambient air temperature for operation	-25...50 °C
ambient air temperature for storage	-40...85 °C

### Offer Sustainability

Not Green Premium product	Not Green Premium product
Compliant - since 0627 - Schneider Electric declaration of conformity	Compliant - since 0627 - Schneider Electric declaration of conformity
Reference not containing SVHC above the threshold	Reference not containing SVHC above the threshold
Need no specific recycling operations	Need no specific recycling operations

Informacije dane u ovoj dokumentaciji sadrže opće opise i/ili tehničke karakteristike o performansama ovdje sadržanih proizvoda. Ova dokumentacija nije namijenjena kao zamjena za niti bi se trebala koristiti za određivanje prikladnosti ili pouzdanosti predmetnih proizvoda za konkretne korisničke primjene. Svaki takav korisnik ili integrator dužan je provesti odgovarajuću i potpunu analizu rizika, procjenu i ispitivanje proizvoda u odnosu na odgovarajuću specifičnu primjenu ili uporabu istog. Niti društvo Schneider Electric Industries SAS niti bilo koje od njegovih povezanih poduzeća ili podružnica neće preuzeti obvezu ili snositi odgovornost za pogrešnu upotrebu ovdje sadržanih informacija.