

170ENT11001

Modicon Momentum - Ethernet komunikacijski adapter – 10/100 Mbit/s



Glavno

Range of product	Modicon Momentum automation platform
Product or component type	Ethernet TCP/IP communication adaptor
Communication port protocol	Ethernet TCP/IP
Method of access	Master/slave Peer to peer
Transmission rate	10/100 Mbit/s
Transmission support medium	Shielded twisted pairs cable

Komplementarno

Module configuration	BOOTP server to assign IP parameters
Topology	Multidrop, star network
Port Ethernet	100BASE-TX
Number of devices per segment	0...32
Cable distance between devices	1000 m without repeater
Addressing	IP address user assigned Unique IEEE global address
Fail state	Fail safe
Control parameter	CRC-32
Supply	From I/O base
Marking	CE
Local signalling	1 LED green Ethernet network 10 Mbits/s (10T) 1 LED green Ethernet network state (ST) 1 LED green module active (RUN) 1 LED yellow Ethernet network 10 Mbits/s (100T)
Electrical connection	1 connector RJ45 for 100BASE-TX
Product weight	0.07 kg

Okolina

product certifications	CSA UL
standards	CSA
IP degree of protection	IP20
protective treatment	TC
resistance to electrostatic discharge	4 kV contact IEC 801-2 8 kV on air IEC 801-2
resistance to electromagnetic fields	10 V/m 80...1000 MHz IEC 801-3
ambient air temperature for operation	0...60 °C
ambient air temperature for storage	-40...85 °C
relative humidity	95 % without condensation
operating altitude	<= 5000 m

Offer Sustainability

Not Green Premium product	Not Green Premium product
Compliant - since 0925 - Schneider Electric declaration of conformity	Compliant - since 0925 - Schneider Electric declaration of conformity
Reference not containing SVHC above the threshold	Reference not containing SVHC above the threshold

Informacije dane u ovoj dokumentaciji sadrže opće opise i/ili tehničke karakteristike o performansama ovdje sadržanih proizvoda. Ova dokumentacija nije namijenjena kao zamjena za niti bi se trebala koristiti za određivanje prikladnosti ili pouzdanosti predmetnih proizvoda za konkretne korisničke primjene. Svaki takav korisnik ili integrator dužan je provesti odgovarajuću i popunnu analizu rizika, procjenu i ispitivanje proizvoda u odnosu na odgovarajuću specifičnu primjenu ili uporabu istog. Niti društvo Schneider Electric, Industries SAS niti bilo koje od njegovih povezanih poduzeća ili podružnica neće preuzeti obvezu ili snositi odgovornost za pogrešnu upotrebu ovdje sadržanih informacija.

Contractual warranty

Warranty period

18 months