



## Glavno

Range	Acti 9
Product or component type	Residual current circuit breaker (RCCB)
Device short name	REDs
Protection type	Recloser
Poles description	4P
Neutral position	Left
Signal contacts composition	1NO or 1NC or intermittent 1 Hz
[In] rated current	40 A
Earthing system	TN-S TT
Network type	AC
Earth-leakage sensitivity	30 mA

## Komplementarno

Device location in system	Outgoer
Network frequency	50 Hz
[Ue] rated operational voltage	400 V AC 50 Hz phase to neutral
Reset	Fault reset earth leakage
Test function	Manual at 170 V
Earth-leakage protection time delay	Instantaneous
Earth-leakage protection class	Type A
[Im] rated making and breaking capacity	Idm 630 A 400 V
Rated conditional short-circuit current	C120: Inc 10 kA 25 A GL63: Inc 6 kA 25 A gL NG125: Inc 10 kA 25 A DPN: Inc 6 kA 25 A DPNN: Inc 6 kA 25 A IC60: Inc 10 kA 25 A GL80: Inc 6 kA 25 A gL
[Ui] rated insulation voltage	500 V
[Uimp] rated impulse withstand voltage	4 kV
Control type	Toggle
Local signalling	2 LEDs Recloser : ON/OFF indication Residual current device : ON/OFF indication
Type of setting	Insulation fault presence monitoring Max nb of consecutive restart Min interval between 2 closings Nb of restart operations Recloser Restart cycle Restart in event of transient insulation fault Stopping restart cycle if insulation fault present
Signalling circuit voltage	AC: 5...230 V DC: 5...230 V
Signalling output current	0.6 mA min 100 mA max, cos phi =1
Mounting mode	Fixed
Mounting support	35 mm symmetrical DIN rail
9 mm pitches	14
Height	98 mm

Width	125 mm
Depth	79.5 mm
Embedding depth	73.5 mm
Product weight	0.67 kg
Mechanical durability	4000 cycles open-close
Connections - terminals	Guard tunnel terminal 35 mm <sup>2</sup> rigid Guard tunnel terminal 35 mm <sup>2</sup> flexible
Auxiliary connection terminal	Tunnel type terminal flexible 2.5 mm <sup>2</sup> Tunnel type terminal rigid 2.5 mm <sup>2</sup>
Wire stripping length	12 mm
Tightening torque	Power circuit: 2 N.m Signaling: 0.4 N.m

## Okolina

standards	EN 61008 IEC 61008
IP degree of protection	IP20
electromagnetic compatibility	8/20 μs wave immunity 250 A
tropicalisation	2
relative humidity	95 % ( 55 °C )
ambient air temperature for operation	-5...40 °C
ambient air temperature for storage	-20...60 °C

## Offer Sustainability

Not Green Premium product	Not Green Premium product
Compliant - since 0901 - Schneider Electric declaration of conformity	Compliant - since 0901 - Schneider Electric declaration of conformity
Reference not containing SVHC above the threshold	Reference not containing SVHC above the threshold