



Glavno

Range	Acti 9
Product or component type	Residual current circuit breaker (RCCB)
Device short name	REDtest
Protection type	Recloser
Poles description	2P
Neutral position	Right
Signal contacts composition	1NO or intermittent 1 Hz
[In] rated current	40 A
Earthing system	TN-S TT
Network type	AC
Earth-leakage sensitivity	30 mA

Komplementarno

Device location in system	Outgoer
Network frequency	50 Hz
[Ue] rated operational voltage	230 V AC 50 Hz phase to neutral
Reset	Fault reset earth leakage
Test function	Manual at 195 V Auto test
Earth-leakage protection time delay	Instantaneous
Earth-leakage protection class	Type A
Leakage resistance	120 kOhm
[Im] rated making and breaking capacity	Idm 630 A 230 V
Rated conditional short-circuit current	C120: Inc 6 kA 40 A C32: Inc 4.5 kA 40 A C60: Inc 6 kA 40 A DT40: Inc 6 kA 40 A DT40N: Inc 6 kA 40 A GL63: Inc 6 kA 40 A gL K60: Inc 6 kA 40 A NG125: Inc 6 kA 40 A
[Ui] rated insulation voltage	500 V
[Uimp] rated impulse withstand voltage	4 kV
Control type	Toggle
Local signalling	2 LEDs Recloser and autotest : ON/OFF indication Residual current device : ON/OFF indication
Type of setting	Autotest Insulation fault presence monitoring Max nb of consecutive restart Min interval between 2 closings Nb of restart operations Recloser Restart cycle Restart in event of transient insulation fault Stopping restart cycle if insulation fault present
Signalling circuit voltage	AC: 12...230 V
Signalling output current	0.6 mA min 100 mA max, cos phi =1
Mounting mode	Fixed
Mounting support	35 mm symmetrical DIN rail

Informacije dane u ovoj dokumentaciji sadrže opće opise i/ili tehničke karakteristike o performansama ovdje sadržanih proizvoda. Ova dokumentacija nije namijenjena kao zamjena za niti bi se trebala koristiti za određivanje prikladnosti ili pouzdanosti predmetnih proizvoda za konkretne korisničke primjene. Svaki takav korisnik ili integrator dužan je provesti odgovarajuću i potpuniju analizu rizika, procjenu i ispitivanje proizvoda u odnosu na odgovarajuću specifičnu primjenu ili uporabu istog. Niti društvo Schneider Electric, Industries SAS niti bilo koje od njegovih povezanih poduzeća ili podružnica neće preuzeti obvezu ili snositi odgovornost za pogrešnu upotrebu ovdje sadržanih informacija.

9 mm pitches	10
Height	115 mm
Width	89.2 mm
Depth	79.5 mm
Product weight	0.37 kg
Mechanical durability	1000 cycles open-close
Connections - terminals	Guard tunnel terminal 25 mm ² flexible Guard tunnel terminal 35 mm ² rigid
Auxiliary connection terminal	Tunnel type terminal flexible 2.5 mm ² Tunnel type terminal rigid 2.5 mm ²
Wire stripping length	12 mm
Tightening torque	Power circuit: 2 N.m Signaling: 0.4 N.m

Okolina

standards	EN 61008 IEC 61008
IP degree of protection	IP20
electromagnetic compatibility	8/20 µs wave immunity 250 A
tropicalisation	2
relative humidity	95 % (55 °C)
ambient air temperature for operation	-5...40 °C
ambient air temperature for storage	-20...60 °C

Offer Sustainability

Not Green Premium product	Not Green Premium product
Compliant - since 0620 - Schneider Electric declaration of conformity	Compliant - since 0620 - Schneider Electric declaration of conformity
Reference not containing SVHC above the threshold	Reference not containing SVHC above the threshold
Need no specific recycling operations	Need no specific recycling operations

Contractual warranty

Warranty period	18 months
-----------------	-----------