



### Glavno

Range	Acti 9
Product name	Acti 9 NG125NA
Product or component type	Switch disconnecter
Device short name	NG125NA
Device application	Distribution Making and breaking under load
Poles description	3P
Number of protected poles	3
Utilisation category	AC-22A conforming to IEC 60947-3 AC-22B conforming to IEC 60947-3 AC-23B conforming to IEC 60947-3
Suitability for isolation	Yes conforming to IEC 60947-3

### Komplementarno

[Ie] rated operational current	63 A AC 50/60 Hz 500 V
[Ue] rated operational voltage	500 V AC 50/60 Hz
[Icm] rated short-circuit making capacity	2 kA switch-disconnector alone
[Icw] rated short-time withstand current	IEC 60947-3
[Ui] rated insulation voltage	690 V AC 50/60 Hz conforming to IEC 60947-3
[Uimp] rated impulse withstand voltage	8 kV conforming to IEC 60947-3
Contact position indicator	Yes
Control type	Toggle Manual tripping test
Local signalling	ON/OFF indication Trip indicator
Mounting mode	Fixed
Mounting support	35 mm symmetrical DIN rail
9 mm pitches	9
Height	103 mm
Width	81 mm
Depth	81 mm
Product weight	0.72 kg
Colour	Black
Mechanical durability	20000 cycles
Electrical durability	Category A (except AC20, DC20): 1500 cycles AC 50/60 Hz conforming to IEC 60947-3 Category B (except AC20, DC20): 300 cycles AC 50/60 Hz conforming to IEC 60947-3
Provision for padlocking	Padlockable
Locking options description	Integrated padlocking
Connections - terminals	Tunnel type terminals top or bottom 1...35 mm <sup>2</sup> flexible
Wire stripping length	20 mm top or bottom power circuit
Tightening torque	3.5 N.m top or bottom power circuit

### Okolina

standards	EN 60947-3 IEC 60947-3
product certifications	VDE
IP degree of protection	IP20 conforming to IEC 60529 IP40 conforming to IEC 60529

Informacije dane u ovoj dokumentaciji sadrže opće opise i/ili tehničke karakteristike o performansama ovdje sadržanih proizvoda. Ova dokumentacija nije namijenjena kao zamjena za niti bi se trebala koristiti za određivanje prikladnosti ili pouzdanosti predmetnih proizvoda za konkretne korisničke primjene. Svaki takav korisnik ili integrator dužan je provesti odgovarajuću i poplunu analizu rizika, procjenu i ispitivanje proizvoda u odnosu na odgovarajuću specifičnu primjenu ili uporabu istog. Niti društvo Schneider Electric Industries SAS niti bilo koje od njegovih povezanih poduzeća ili podružnica neće preuzeti obvezu ili snositi odgovornost za pogrešnu upotrebu ovdje sadržanih informacija.

IK degree of protection	IK05
pollution degree	3 conforming to IEC 60947-3
tropicalisation	2 conforming to IEC 60068-1
ambient air temperature for operation	-10...60 °C
ambient air temperature for storage	-40...70 °C

### Contractual warranty

Warranty period	18 months
-----------------	-----------