

Product data sheet

Characteristics

ATER tim

29376

automatski kontroler – BA – 220..240 V



Main

Product name	BA
Product or component type	Control unit

Complementary

[Us] rated supply voltage	220...240 V AC 50/60 Hz
Operating mode	Stop (both normal and replacement source off) Forced operation on normal source Forced operation on replacement source Automatic operation
Interlocked device	Compact NS630b...1600 Masterpact NW Compact NS100...630 Masterpact NT
Selection modes	Circuit breaker on R Circuit breaker on N
Test function	By opening the P25M circuit breaker supplying the controller
Complementary function	Additional contact: transfer to replacement source only if contact is closed Voluntary transfer to replacement source (e.g. energy management commands)
Local signalling	Fault trip Off On
Input type	Contacts customer voluntary order to transfer to source R
Output type	Contacts customer indication of operation in automatic or stop mode
[Ith] conventional free air thermal current	8 A
[Ie] rated operational current	AC-12 4 A AC 440 V AC-12 5 A AC 380/415 V DC-13 2 A 24 V

Environment

Standards	IEC 947-5-1
IP degree of protection	Connectors IP20 EN 60529 Front IP40 EN 60529 Side IP30 EN 60529
IK degree of protection	Front IK07 EN 50102

The information provided in this documentation contains general descriptions and/or technical characteristics of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Offer Sustainability

Status održive ponude	Proizvod Green Premium
Uredba REACH	Izjava REACH
Direktiva EU RoHS	Sukladno Izjava EU RoHS
Bez žive	Da
Informacije o RoHS izuzeću	Da
Propis RoHS za Kinu	Izjava RoHS Za Kinu
Izjava o očuvanju okoliša	Ekološki Profil Proizvoda
Profil cirkularnosti	Informacije O Kraju Vijeka Trajanja
WEEE	Proizvod se na tržištima EU mora odlagati u skladu sa specifičnim propisima o prikupljanju otpada; nikako se ne smije odlagati s komunalnim otpadom.

Contractual warranty

Jamstvo	18 months
---------	-----------