



Glavno

Device short name	OF SD SDE SDV
Product or component type	Auxiliary contact
Range compatibility	Compact NS1600b...3200 Compact NS630b...1600 Compact Compact NSX Compact Compact NG Compact Compact NR Easypact EasyPact CVS Compact Compact INS Compact Compact INSE Compact Compact INSJ Compact Compact INV
Offer type	C4 C5
Signal contacts composition	1 NO/NC

Komplementarno

Auxiliary contacts type	Standard
Auxiliary contacts operation	Early-break Early-make
Mounting mode	Clip-on
[I _{th}] conventional free air thermal current	6 A
[I _e] rated operational current	Utilisation category AC-12: 6 A network: AC 50/60 Hz at 110 V Utilisation category AC-12: 6 A network: AC 50/60 Hz at 220/240 V Utilisation category AC-12: 6 A network: AC 50/60 Hz at 24 V Utilisation category AC-12: 6 A network: AC 50/60 Hz at 380/440 V Utilisation category AC-12: 6 A network: AC 50/60 Hz at 48 V Utilisation category AC-12: 6 A network: AC 50/60 Hz at 480 V Utilisation category AC-12: 6 A network: AC 50/60 Hz at 660/690 V Utilisation category AC-15: 0.1 A network: AC 50/60 Hz at 660/690 V Utilisation category AC-15: 1.5 A network: AC 50/60 Hz at 480 V Utilisation category AC-15: 2 A network: AC 50/60 Hz at 380/440 V Utilisation category AC-15: 4 A network: AC 50/60 Hz at 220/240 V Utilisation category AC-15: 5 A network: AC 50/60 Hz at 110 V Utilisation category AC-15: 6 A network: AC 50/60 Hz at 24 V Utilisation category AC-15: 6 A network: AC 50/60 Hz at 48 V Utilisation category DC-12: 0.3 A network: DC at 250 V Utilisation category DC-12: 0.6 A network: DC at 110 V Utilisation category DC-12: 2.5 A network: DC at 48 V Utilisation category DC-12: 6 A network: DC at 24 V Utilisation category DC-14: 0.03 A network: DC at 250 V Utilisation category DC-14: 0.05 A network: DC at 110 V Utilisation category DC-14: 0.2 A network: DC at 48 V Utilisation category DC-14: 1 A network: DC at 24 V
Minimum load	100 mA at 24 V
Accessory / separate part category	Spare part Compact NS630b...1600 Spare part Compact NS1600b...3200

Okolina

Contractual warranty

Warranty period	18 months
-----------------	-----------

Informacije dane u ovoj dokumentaciji sadrže opće opise i/ili tehničke karakteristike o performansama ovdje sadržanih proizvoda. Ova dokumentacija nije namijenjena kao zamjena za niti bi se trebala koristiti za određivanje prikladnosti ili pouzdanosti predmetnih proizvoda za konkretne korisničke primjene. Svaki takav korisnik ili integrator dužan je provesti odgovarajuću i popiplunu analizu rizika, procjenu i ispitivanje specifičnu primjenu ili uporabu istog. Niti društvo Schneider Electric, Industries SAS niti bilo koje od njegovih povezanih poduzeća ili podružnica neće preuzeti obvezu ili snositi odgovornost za pogrešnu upotrebu ovdje sadržanih informacija.