

## 33234

prekidač Compact NS800N – 4 pola – 800 A – fiksni  
- bez jed. za prekid



### Glavno

Range of product	NS630b...1600
Product or component type	Basic frame
Device short name	Compact NS800N
Device application	Distribution
Circuit breaker name	Compact NS800N
Poles description	4P
Neutral position	Left
Network type	AC
Breaking capacity code	N
Suitability for isolation	Yes conforming to IEC 60947-2
Utilisation category	Category B

### Komplementarno

Network frequency	50/60 Hz
Control type	Rotary handle Toggle
Mounting mode	Fixed
Mounting support	Backplate
Upside connection	Front
Downside connection	Front
[In] rated current	800 A ( 50 °C )
[Ui] rated insulation voltage	800 V AC 50/60 Hz conforming to IEC 60947-2
[Uimp] rated impulse withstand voltage	8 kV conforming to IEC 60947-2
[Ue] rated operational voltage	690 V AC 50/60 Hz conforming to IEC 60947-2
Circuit breaker CT rating	800 A
Breaking capacity	Icu 30 kA at 660/690 V AC 50/60 Hz conforming to IEC 60947-2 Icu 40 kA at 500/525 V AC 50/60 Hz conforming to IEC 60947-2 Icu 50 kA at 380/415 V AC 50/60 Hz conforming to IEC 60947-2 Icu 50 kA at 440 V AC 50/60 Hz conforming to IEC 60947-2 Icu 85 kA at 220/240 V AC 50/60 Hz conforming to IEC 60947-2
[Ics] rated service breaking capacity	Ics 30 kA 660/690 V AC 50/60 Hz manual operation conforming to IEC 60947-2 Ics 40 kA 500/525 V AC 50/60 Hz manual operation conforming to IEC 60947-2 Ics 50 kA 220/240 V AC 50/60 Hz manual operation conforming to IEC 60947-2 Ics 50 kA 380/415 V AC 50/60 Hz manual operation conforming to IEC 60947-2 Ics 50 kA 440 V AC 50/60 Hz manual operation conforming to IEC 60947-2
Protection type	Without protection
Mechanical durability	10000 cycles conforming to IEC 60947-2
Electrical durability	2000 cycles 690 V AC 50/60 Hz In conforming to IEC 60947-2 4000 cycles 690 V AC 50/60 Hz In/2 conforming to IEC 60947-2 5000 cycles 440 V AC 50/60 Hz In conforming to IEC 60947-2 6000 cycles 440 V AC 50/60 Hz In/2 conforming to IEC 60947-2
Connection pitch	70 mm
[Icw] rated short-time withstand current	19.2 kA ( 1 s ) conforming to IEC 60947-2
Integral instant protection	40 kA
Height	327 mm
Width	280 mm
Depth	147 mm

Informacije dane u ovoj dokumentaciji sadrže opće i/ili tehničke karakteristike o performansama ovdje sadržanih proizvoda. Ova dokumentacija nije namijenjena kao zamjena za niti bi se trebala koristiti za određivanje prikladnosti ili pouzdanosti predmetnih proizvoda za konkretne korisničke primjene. Svaki takav korisnik ili integrator dužan je provesti odgovarajuću i potpunu analizu rizika, procjenu i ispitivanje proizvoda u odnosu na odgovarajuću specifičnu primjenu ili uporabu istog. Niti društvo Schneider Electric, Industries SAS niti bilo koje od njegovih povezanih poduzeća ili podružnica neće preuzeti obvezu ili snositi odgovornost za pogrešnu upotrebu ovdje sadržanih informacija.

## Okolina

standards	IEC 60947-2
product certifications	ASEFA ASTA LCIE
power losses	15 W
IP degree of protection	IP40 conforming to IEC 60529
IK degree of protection	IK07 conforming to EN 50102
pollution degree	3 conforming to IEC 60947
ambient air temperature for operation	-25...70 °C
ambient air temperature for storage	-50...85 °C

## Offer Sustainability

Green Premium product	Green Premium product
Compliant - since 1622 - Schneider Electric declaration of conformity	Compliant - since 1622 - Schneider Electric declaration of conformity
Reference not containing SVHC above the threshold	Reference not containing SVHC above the threshold
Available	Available
Need no specific recycling operations	Need no specific recycling operations

## Contractual warranty

Warranty period	18 months
-----------------	-----------