



Glavno

Range of product	Masterpact NT
Product or component type	Basic frame
Device short name	Masterpact NT06
Circuit breaker name	Masterpact NT06L1
Poles description	3P
Network type	AC
Breaking capacity code	L1
Suitability for isolation	Yes conforming to IEC 60947-2
Utilisation category	Category A

Komplementarno

Network frequency	50/60 Hz
Control type	Push-button
Mounting mode	Fixed
[In] rated current	630 A (40 °C)
[Ui] rated insulation voltage	1000 V AC 50/60 Hz conforming to IEC 60947-2
[Uimp] rated impulse withstand voltage	12 kV conforming to IEC 60947-2
[Icm] rated short-circuit making capacity	220 kA 525 V AC 50/60 Hz 286 kA 440 V AC 50/60 Hz 330 kA 220/415 V AC 50/60 Hz 52 kA 690 V AC 50/60 Hz
[Ue] rated operational voltage	690 V AC 50/60 Hz conforming to IEC 60947-2
Circuit breaker CT rating	630 A
Breaking capacity	100 kA Icu at 525 V AC 50/60 Hz conforming to IEC 60947-2 130 kA Icu at 440 V AC 50/60 Hz conforming to IEC 60947-2 25 kA Icu at 690 V AC 50/60 Hz conforming to IEC 60947-2 150 kA Icu at 220...240 V AC 50/60 Hz conforming to IEC 60947-2 150 kA Icu at 380...415 V AC 50/60 Hz conforming to IEC 60947-2
[Ics] rated service breaking capacity	Ics 100 kA 525 V AC 50/60 Hz conforming to IEC 60947-2 Ics 130 kA 440 V AC 50/60 Hz conforming to IEC 60947-2 Ics 150 kA 220/415 V AC 50/60 Hz conforming to IEC 60947-2 Conforming to IEC 60947-2
Protection type	Without protection
Mechanical durability	12500 cycles without maintenance conforming to IEC 60947-2
Electrical durability	2000 cycles 690 V AC 50/60 Hz without maintenance conforming to IEC 60947-2 3000 cycles 440 V AC 50/60 Hz without maintenance conforming to IEC 60947-2 AC-23A: 3000 cycles 690 V AC 50/60 Hz without maintenance conforming to IEC 60947-2 AC-23A: 6000 cycles 440 V AC 50/60 Hz without maintenance conforming to IEC 60947-2 AC-3: 6000 cycles 440 V AC 50/60 Hz without maintenance conforming to IEC 60947-2
Connection pitch	70 mm
[Icw] rated short-time withstand current	10 kA (0.5 s) conforming to IEC 60947-2
Integral instant protection	5.67...6.93 kA
Maximum breaking time	9 ms
Closing response time	< 50 ms
Height	301 mm
Width	276 mm
Depth	196 mm

Informacije dane u ovoj dokumentaciji sadrže opće opise i/ili tehničke karakteristike o performansama ovdje sadržanih proizvoda. Ova dokumentacija nije namijenjena kao zamjena za niti bi se trebala koristiti za određivanje prikladnosti ili pouzdanosti predmetnih proizvoda za konkretne korisničke primjene. Svaki takav korisnik ili integrator dužan je provesti odgovarajuću i popunnu analizu rizika, procjenu i ispitivanje proizvoda u odnosu na odgovarajuću specifičnu primjenu ili uporabu istog. Niti društvo Schneider Electric, Industries SAS niti bilo koje od njegovih povezanih poduzeća ili podružnica neće preuzeti obvezu ili snositi odgovornost za pogrešnu upotrebu ovdje sadržanih informacija.

Okolina

standards	IEC 60947-2
product certifications	ASEFA LCIE
pollution degree	3 conforming to IEC 60664-1
ambient air temperature for operation	-25...70 °C
ambient air temperature for storage	-40...85 °C

Contractual warranty

Warranty period	18 months
-----------------	-----------