



Main

Range	Vigilohm
Range of product	Vigilohm
Device short name	HRP
Product or component type	Hospital remote panel
Range compatibility	Vigilohm IM IM20-H
Sound signalling	Insulation or electrical fault buzzer adjustable 80 dB

Complementary

Auxiliary supply voltage	24 V DC
Current consumption	65 mA
Material	Plastic
Control type	Push-button test installation insulation Push-button stop alarm buzzer
Local signalling	Insulation fault indicator light (narančasto) Electrical fault indicator light (red) Normal operation indicator light (green)
Neto težina	0,5 kg
Maksimalna širina	170 mm
Maksimalna visina	170 mm
Maksimalna dubina	20 mm

Environment

IP degree of protection	IP54
IK degree of protection	IK08
Operating altitude	2000 m
Relative humidity	90 %
Standards	IEC 60364-7-710 medical location IEC 61557-8 safety IEC 60601-1 medical electrical equipment
Ambient air temperature for operation	0...40 °C
Ambient air temperature for storage	-25...70 °C

Broj pakirnih jedinica

Vrsta pakirne jedinice Paketa 1	PCE
Vrsta pakirne jedinice Paketa 2	S04

Offer Sustainability

REACH, bez SVHC	Da
Direktiva EU RoHS	Sukladno Izjava EU RoHS
Bez otrovnih teških metala	Da
Bez žive	Da
Informacije o RoHS izuzeću	Da
Propis RoHS za Kinu	Izjava RoHS Za Kinu

Contractual warranty

Jamstvo	18 months
---------	-----------