



## Glavno

Range	Vigirex
Device short name	TA30
Product or component type	Earth leakage current sensor
Device application	Equipment monitoring and control
Range compatibility	Vigirex RH plug-in relay
[Ie] rated operational current	65 A

## Komplementarno

Current transformer type	A type closed toroid
Network type	AC DC
Network frequency	45...440 Hz
[Ui] rated insulation voltage	1000 V
Transformer ratio	1/1000
[Icw] rated short-time withstand current	100 kA / 0.5 s
Residual short-circuit withstand current	85 kA / 0.5 s conforming to IEC 60947-2
Overvoltage category	IV
[Uimp] rated impulse withstand voltage	12 kV
Mounting mode	Clip-on Vigirex relay Fixed plain backplate Fixed profiled sheet metal Fixed slotted backplate Clip-on DIN rail
Calorific value	0.98 MJ
Connections - terminals	Screw connection : >= 0.22 mm <sup>2</sup>
Diameter	30 mm (inner)
Cable outer diameter	15 mm: 25 mm <sup>2</sup> (maximum)
Product weight	0.12 kg
Height	82 mm
Width	60 mm
Depth	29 mm

## Okolina

IP degree of protection	IP30 Connectors: IP20
environmental characteristic	Exposure to damp heat not in service conforming to IEC 60068-2-30: 28 cycles 25...55 °C, RH 95 % Salt mist conforming to IEC 60068-2-52: Kb/2 Exposure to damp heat in service conforming to IEC 60068-2-56: 48 hours: category C2
pollution degree	Level 3 conforming to IEC 60664-1
ambient air temperature for operation	-35...70 °C
ambient air temperature for storage	-55...85 °C

Informacije dane u ovoj dokumentaciji sadrže opće opise i/ili tehničke karakteristike o performansama ovdje sadržanih proizvoda. Ova dokumentacija nije namijenjena kao zamjena za niti bi se trebala koristiti za određivanje prikladnosti ili pouzdanosti predmetnih proizvoda za konkretne korisničke primjene. Svaki takav korisnik ili integrator dužan je provesti odgovarajuću i potpunu analizu rizika, procjenu i ispitivanje proizvoda u odnosu na odgovarajuću specifičnu primjenu ili uporabu istog. Niti društvo Schneider Electric Industries SAS niti bilo koje od njegovih povezanih podružnica neće preuzeti obvezu ili snositi odgovornost za pogrešnu upotrebu ovdje sadržanih informacija.

## Offer Sustainability

Green Premium product	Green Premium product
Compliant - since 0901 - Schneider Electric declaration of conformity	Compliant - since 0901 - Schneider Electric declaration of conformity
Reference not containing SVHC above the threshold	Reference not containing SVHC above the threshold
Available	Available
Available	Available

## Contractual warranty

Warranty period	18 months
-----------------	-----------