

## Podatkovni list proizvoda

### Karakteristike

## 81195

Industrijska utičnica PratiKa – 125 A – 3P + N + E – 380...415 V AC – IP67



### Glavno

Range	PratiKa
Product or component type	Socket
Device short name	PratiKa socket
Plug, socket category	Low voltage
Poles description	3P + N + E
Network type	AC
Outlet standard	Industrial

### Komplementarno

Mounting mode	Wall-mounted
Plug, socket, control station shape	Angled
[In] rated current	125 A
[Ue] rated operational voltage	380...415 V
Network frequency	50/60 Hz
Ground lug clockwise position	6 h
Plug, socket material	Housing: self-extinguishing engineering polymer
Contacts material	Pins: stainless steel Springs: stainless steel Sleeves: nickel plated brass
Connections - terminals	Captive screws, completely loosened
Cable cross section	16...70 mm <sup>2</sup>
Cable entry	Cable gland
Thread type	Pg 48
Product weight	2.4 kg
Base dimension	114 x 224 mm
Height	340 mm
Width	114 mm
Depth	213 mm
Colour	Grey ( RAL 7035 )
Voltage colour	Red

### Okolina

standards	EN 60309-1 EN 60309-2
IP degree of protection	IP67 conforming to IEC 60529
IK degree of protection	IK08 conforming to EN 62262
fire resistance	850 °C conforming to IEC 60695-2-11
relative humidity	50 % ( 40 °C ) 70 % ( 30 °C ) 90 % ( 20 °C )
ambient air temperature for operation	35 °C ( 86400 s )

### Contractual warranty

Warranty period	18 months
-----------------	-----------

