

Podatkovni list proizvoda

Karakteristike

81390

Utikač PratiKa, vijčani spoj – ravni – 125 A – 2P + E
– 200...250 V AC – IP67



Glavno

| | |
|---------------------------|--------------|
| Range | PratiKa |
| Product or component type | Wander plug |
| Device short name | PratiKa plug |
| Plug, socket category | Low voltage |
| Poles description | 2P + E |
| Network type | AC |
| Outlet standard | Industrial |

Komplementarno

| | |
|-------------------------------------|---|
| Plug, socket, control station shape | Straight |
| [In] rated current | 125 A |
| [Ue] rated operational voltage | 200...250 V |
| Network frequency | 50/60 Hz |
| Ground lug clockwise position | 6 h |
| Plug, socket material | Self-extinguishing engineering polymer housing: |
| Contacts material | Nickel plated brass pins: |
| Connections - terminals | Captive screws |
| Cable cross section | 16...70 mm ² |
| Cable outer diameter | 26...48 mm |
| Cable entry | Cable gland |
| Thread type | Pg 48 |
| Product weight | 1.18 kg |
| Height | 325 mm |
| Width | 131 mm |
| Depth | 131 mm |
| Colour | Grey (RAL 7035) |
| Voltage colour | Blue |

Okolina

| | |
|---------------------------------------|--|
| standards | IEC 60309-1 IEC 60309-2 |
| IP degree of protection | IP67 conforming to IEC 60529 |
| IK degree of protection | IK08 conforming to EN 62262 |
| fire resistance | 850 °C conforming to IEC 60695-2-11 |
| relative humidity | 50 % (40 °C) 70 % (30 °C) 90 % (20 °C) |
| operating altitude | 2000 m |
| ambient air temperature for operation | 35 °C (86400 s) -25...40 °C |

Contractual warranty

| | |
|-----------------|-----------|
| Warranty period | 18 months |
|-----------------|-----------|