



Glavno

| | |
|---------------------------|---------------------|
| Range | PratiKa |
| Product or component type | Plug |
| Device short name | Panel mounted plugs |
| Plug, socket category | Low voltage |
| Poles description | 3P + E |
| Network type | AC |
| Outlet standard | Industrial |

Komplementarno

| | |
|-------------------------------------|-------------------------------------|
| Mounting mode | Panel-mounted |
| Plug, socket, control station shape | Straight |
| [In] rated current | 125 A |
| [Ue] rated operational voltage | 100...130 V |
| Network frequency | 50/60 Hz |
| Ground lug clockwise position | 4 h |
| Plug, socket material | Self-extinguishing polymer housing: |
| Contacts material | Nickel plated brass pins: |
| Connections - terminals | Captive screws |
| Cable cross section | 16...70 mm ² |
| Thread type | Pg 48 |
| Product weight | 1.5 kg |
| Base dimension | 110 x 114 mm |
| Height | 325 mm |
| Width | 131 mm |
| Depth | 131 mm |
| Colour | Grey (RAL 7035) |
| Voltage colour | Yellow |

Okolina

| | |
|---------------------------------------|--|
| standards | IEC 60309-1 IEC 60309-2 |
| IP degree of protection | IP67 conforming to IEC 60529 |
| IK degree of protection | IK08 conforming to EN 62262 |
| fire resistance | 850 °C conforming to IEC 60695-2-11 |
| relative humidity | 50 % (40 °C) 70 % (30 °C) 90 % (20 °C) |
| operating altitude | 2000 m |
| ambient air temperature for operation | 35 °C (86400 s) -25...40 °C |

Informacije dane u ovoj dokumentaciji sadrže opće opisne i/ili tehničke karakteristike o performansama ovdje sadržanih proizvoda. Ova dokumentacija nije namijenjena kao zamjena za niti bi se trebala koristiti za određivanje prikladnosti ili pouzdanosti predmetnih proizvoda za konkretne korisničke primjene. Svaki takav korisnik ili integrator dužan je provesti odgovarajuću i potpunu analizu rizika, procjenu i ispitivanje proizvoda u odnosu na odgovarajuću specifičnu primjenu ili uporabu istog. Niti društvo Schneider Electric Industries SAS niti bilo koje od njegovih povezanih podružnica ili podružnica neće preuzeti obvezu ili snositi odgovornost za pogrešnu upotrebu ovdje sadržanih informacija.