

## Podatkovni list proizvoda

### Karakteristike

# 82404

Utičnica PratiKa, vijčani spoj – ravna – 16 A – 3P – 40...50 V AC – IP44



### Glavno

Range	PratiKa
Product or component type	Wander socket
Device short name	PratiKa socket
Plug, socket category	Extra-low voltage
Poles description	3P
Network type	AC
Outlet standard	Industrial

### Komplementarno

Plug, socket, control station shape	Straight
[In] rated current	16 A
[Ue] rated operational voltage	40...50 V
Network frequency	50/60 Hz
Secondary keyway clockwise position	12 h
Plug, socket material	Self-extinguishing engineering polymer housing:
Contacts material	Stainless steel pins: Nickel plated brass sleeves: Stainless steel springs:
Connections - terminals	Captive screws
Cable cross section	4...10 mm <sup>2</sup>
Cable outer diameter	6...23 mm
Cable entry	Cable gland
Thread type	Pg 21
Product weight	0.201 kg
Height	72 mm
Width	72 mm
Depth	172 mm
Colour	Grey ( RAL 7035 )
Voltage colour	White

### Okolina

standards	IEC 60309-1 IEC 60309-2
IP degree of protection	IP44 conforming to IEC 60529
IK degree of protection	IK08 conforming to EN 62262
fire resistance	850 °C conforming to IEC 60695-2-1
relative humidity	50 % ( 40 °C ) 70 % ( 30 °C ) 90 % ( 20 °C )
ambient air temperature for operation	35 °C ( 86400 s ) -25...40 °C

### Contractual warranty

Warranty period	18 months
-----------------	-----------