



### Glavno

|                           |                   |
|---------------------------|-------------------|
| Range                     | PratiKa           |
| Product or component type | Plug              |
| Device short name         | PratiKa plug      |
| Plug, socket category     | Extra-low voltage |
| Poles description         | 2P                |
| Network type              | DC                |
| Outlet standard           | Industrial        |

### Komplementarno

|                                     |  |
|-------------------------------------|--|
| Mounting mode                       | Wall-mounted                           |
| Plug, socket, control station shape | Angled                                 |
| [In] rated current                  | 16 A                                   |
| [Ue] rated operational voltage      | 20...25 V<br>40...50 V                 |
| Secondary keyway clockwise position | 10 h                                   |
| Plug, socket material               | Self-extinguishing engineering polymer |
| Contacts material                   | Nickel plated brass pins:              |
| Connections - terminals             | Captive screws                         |
| Cable cross section                 | 4...10 mm <sup>2</sup>                 |
| Cable outer diameter                | 6...23 mm                              |
| Thread type                         | Pg 21                                  |
| Product weight                      | 0.157 kg                               |
| Base dimension                      | 70 x 82 mm                             |
| Height                              | 118 mm                                 |
| Width                               | 70 mm                                  |
| Depth                               | 81 mm                                  |
| Colour                              | Grey ( RAL 7035 )                      |
| Voltage colour                      | White                                  |

### Okolina

|                                       |  |
|---------------------------------------|--|
| standards                             | EN 60309-1<br>EN 60309-2                           |
| IP degree of protection               | IP44 conforming to IEC 60529                       |
| IK degree of protection               | IK08 conforming to EN 62262                        |
| fire resistance                       | 850 °C conforming to IEC 60695-2-1                 |
| relative humidity                     | 50 % ( 40 °C )<br>70 % ( 30 °C )<br>90 % ( 20 °C ) |
| operating altitude                    | 2000 m   |
| ambient air temperature for operation | 35 °C ( 86400 s )<br>-25...40 °C                   |

### Contractual warranty

|                 |           |
|-----------------|-----------|
| Warranty period | 18 months |
|-----------------|-----------|

