



Glavno

| | |
|---------------------------|-------------------|
| Range | PratiKa |
| Product or component type | Plug |
| Device short name | PratiKa plug |
| Plug, socket category | Extra-low voltage |
| Poles description | 3P |
| Network type | AC |
| Outlet standard | Industrial |

Komplementarno

| | |
|-------------------------------------|--|
| Mounting mode | Wall-mounted |
| Plug, socket, control station shape | Angled |
| [In] rated current | 32 A |
| [Ue] rated operational voltage | 20...25 V |
| Network frequency | 50/60 Hz |
| Plug, socket material | Self-extinguishing engineering polymer |
| Contacts material | Nickel plated brass pins: |
| Connections - terminals | Captive screws |
| Cable cross section | 4...10 mm ² |
| Cable outer diameter | 6...23 mm |
| Thread type | Pg 21 |
| Product weight | 0.162 kg |
| Base dimension | 70 x 82 mm |
| Height | 118 mm |
| Width | 70 mm |
| Depth | 81 mm |
| Colour | Grey (RAL 7035) |
| Voltage colour | Violet |

Okolina

| | |
|---------------------------------------|--|
| standards | EN 60309-1 EN 60309-2 |
| IP degree of protection | IP44 conforming to IEC 60529 |
| IK degree of protection | IK08 conforming to EN 62262 |
| fire resistance | 850 °C conforming to IEC 60695-2-1 |
| relative humidity | 50 % (40 °C) 70 % (30 °C) 90 % (20 °C) |
| operating altitude | 2000 m |
| ambient air temperature for operation | 35 °C (86400 s) -25...40 °C |

Contractual warranty

| | |
|-----------------|-----------|
| Warranty period | 18 months |
|-----------------|-----------|