



Glavno

Range	PratiKa
Product or component type	Plug
Device short name	PratiKa plug
Plug, socket category	Extra-low voltage
Poles description	2P
Network type	DC
Outlet standard	Industrial

Komplementarno

Mounting mode	Wall-mounted
Plug, socket, control station shape	Angled
[In] rated current	32 A
[Ue] rated operational voltage	20...25 V 40...50 V
Secondary keyway clockwise position	10 h
Plug, socket material	Self-extinguishing engineering polymer
Contacts material	Nickel plated brass pins:
Connections - terminals	Captive screws
Cable cross section	4...10 mm ²
Cable outer diameter	6...23 mm
Thread type	Pg 21
Product weight	0.157 kg
Base dimension	70 x 82 mm
Height	118 mm
Width	70 mm
Depth	81 mm
Colour	Grey (RAL 7035)
Voltage colour	White

Okolina

standards	EN 60309-1 EN 60309-2
IP degree of protection	IP44 conforming to IEC 60529
IK degree of protection	IK08 conforming to EN 62262
fire resistance	850 °C conforming to IEC 60695-2-1
relative humidity	50 % (40 °C) 70 % (30 °C) 90 % (20 °C)
operating altitude	2000 m
ambient air temperature for operation	35 °C (86400 s) -25...40 °C

Contractual warranty

Warranty period	18 months
-----------------	-----------

