

Podatkovni list proizvoda

Karakteristike

83528

Industrijski utikač PratiKa – 16 A – 3P + E – 200...250 V AC – IP44



Glavno

Range	PratiKa
Product or component type	Plug with phase inverter
Device short name	PratiKa plug
Plug, socket category	Low voltage
Poles description	3P + E
Network type	AC
Outlet standard	Industrial

Komplementarno

Mounting mode	Wall-mounted
Plug, socket, control station shape	Angled
[In] rated current	16 A
[Ue] rated operational voltage	200...250 V
Network frequency	50/60 Hz
Ground lug clockwise position	9 h
Plug, socket material	Self-extinguishing engineering polymer
Contacts material	Nickel plated brass pins:
Connections - terminals	Captive screws
Cable cross section	1...4 mm ²
Cable outer diameter	8...15 mm
Product weight	0.26 kg
Base dimension	80 x 100 mm
Height	140 mm
Width	80 mm
Depth	109 mm
Colour	Grey (RAL 7035)
Voltage colour	Blue

Okolina

standards	EN 60309-1 EN 60309-2
IP degree of protection	IP44 conforming to IEC 60529
IK degree of protection	IK08 conforming to EN 62262
fire resistance	850 °C conforming to IEC 60695-2-1
relative humidity	50 % (40 °C) 70 % (30 °C) 90 % (20 °C)
operating altitude	2000 m
ambient air temperature for operation	35 °C (86400 s) -25...40 °C

Contractual warranty

Warranty period	18 months
-----------------	-----------