

## Podatkovni list proizvoda

### Karakteristike

# 83829

## Industrijski utikač PratiKa – 16 A – 3P + N + E – 200...250 V AC – IP44



### Glavno

Range	PratiKa
Product or component type	Plug with phase inverter
Device short name	PratiKa plug
Plug, socket category	Low voltage
Poles description	3P + N + E
Network type	AC
Outlet standard	Industrial

### Komplementarno

Mounting mode	Panel-mounted
Plug, socket, control station shape	90° angled
[In] rated current	16 A
[Ue] rated operational voltage	200...250 V
Network frequency	50/60 Hz
Ground lug clockwise position	9 h
Plug, socket material	Self-extinguishing engineering polymer
Contacts material	Nickel plated brass pins:
Connections - terminals	Captive screws
Cable cross section	1...4 mm <sup>2</sup>
Cable outer diameter	8...15 mm
Product weight	0.229 kg
Base dimension	90 x 100 mm
Height	148 mm
Width	90 mm
Depth	96 mm
Colour	Grey ( RAL 7035 )
Voltage colour	Blue

### Okolina

standards	EN 60309-1 EN 60309-2
IP degree of protection	IP44 conforming to IEC 60529
IK degree of protection	IK08 conforming to EN 62262
fire resistance	850 °C conforming to IEC 60695-2-1
relative humidity	50 % ( 40 °C ) 70 % ( 30 °C ) 90 % ( 20 °C )
operating altitude	2000 m
ambient air temperature for operation	35 °C ( 86400 s ) -25...40 °C

### Contractual warranty

Warranty period	18 months
-----------------	-----------