



Glavno

Range	Acti 9
Product name	Acti 9 iRO
Product or component type	Buzzer
Device short name	IRO

Komplementarno

[Us] rated supply voltage	230 V AC 50/60 Hz
Power consumption in VA	5 VA
Mounting mode	Fixed
Mounting support	35 mm symmetrical DIN rail
9 mm pitches	2
Height	81 mm
Width	18 mm
Depth	72 mm
Product weight	64 g
Colour	White
Auxiliary connection terminal	Tunnel type terminals rigid < 4 mm ² Tunnel type terminals flexible < 4 mm ² Tunnel type terminals flexible with ferrule < 4 mm ²
Wire stripping length	12 mm (bottom)
Tightening torque	1.3 N.m

Okolina

noise level	70 dB
type of sound	Buzzer
IP degree of protection	IP20 conforming to IEC 60529 IP40 (in modular enclosure) conforming to IEC 60529
ambient air temperature for operation	-10...40 °C
ambient air temperature for storage	-25...60 °C

Offer Sustainability

Not Green Premium product	Not Green Premium product
Compliant - since 0627 - Schneider Electric declaration of conformity	Compliant - since 0627 - Schneider Electric declaration of conformity
Reference not containing SVHC above the threshold	Reference not containing SVHC above the threshold

Contractual warranty

Warranty period	18 months
-----------------	-----------

Informacije dane u ovoj dokumentaciji sadrže opće opise i/ili tehničke karakteristike o performansama ovdje sadržanih proizvoda. Ova dokumentacija nije namijenjena kao zamjena za niti bi se trebala koristiti za određivanje prikladnosti ili pouzdanosti predmetnih proizvoda za konkretne korisničke primjene. Svaki takav korisnik ili integrator dužan je provesti odgovarajuću i potpunu analizu rizika, procjenu i ispitivanje proizvoda u odnosu na odgovarajuću specifičnu primjenu ili uporabu istog. Niti društvo Schneider Electric, Industries SAS niti bilo koje od njegovih povezanih poduzeća ili podružnica neće preuzeti obvezu ili snositi odgovornost za pogrešnu upotrebu ovdje sadržanih informacija.