

## A9A26478

oslobađanje napona – iMX – jedinica za isklapanje –  
12..24 V AC



### Glavno

Range	Acti 9
Product or component type	Shunt trip release
Device short name	iMX
[Uc] control circuit voltage	12...24 V AC 50/60 Hz 12...24 V DC
9 mm pitches	2
Product compatibility	IC60 IID Single terminal Double terminal ISW-NA IDPN Vigi ARA RCA

### Komplementarno

Range compatibility	Acti 9: Acti 9 iDPN (China version) Acti 9: Acti 9 iDPN Vigi Acti 9: Acti 9 iC40 Acti 9: Acti 9 iC65 Acti 9: Acti 9 ARA Acti 9: Acti 9 iID Acti 9: Acti 9 ISW-NA Acti 9: Acti 9 RCA Acti 9: Acti 9 iC60
Local signalling	Action indicator
Mounting mode	Clip-on
Mounting support	DIN rail
Width	18 mm
Colour	White
Connections - terminals	Clamp terminal 1 cable(s) 6 mm <sup>2</sup> rigid Clamp terminal 2 cable(s) 2.5 mm <sup>2</sup> rigid Clamp terminal 1 cable(s) 4 mm <sup>2</sup> flexible Clamp terminal 2 cable(s) 2.5 mm <sup>2</sup> flexible with cable end cable end
Tightening torque	1 N.m

### Okolina

standards	EN/IEC 60947-5-1
tropicalisation	2 conforming to EN/IEC 60947-5-1
relative humidity	95 % at 55 °C
ambient air temperature for operation	-25...50 °C
ambient air temperature for storage	-40...85 °C

### Offer Sustainability

Green Premium product	Green Premium product
Compliant - since 1216 - Schneider Electric declaration of conformity	Compliant - since 1216 - Schneider Electric declaration of conformity
Reference not containing SVHC above the threshold	Reference not containing SVHC above the threshold
Available	Available
Need no specific recycling operations	Need no specific recycling operations

Informacije dane u ovoj dokumentaciji sadrže opće opise i/ili tehničke karakteristike o performansama ovdje sadržanih proizvoda.  
Ova dokumentacija nije namijenjena kao zamjena za niti bi se trebala koristiti za određivanje prikladnosti ili pouzdanosti predmetnih proizvoda za konkretne korisničke primjene.  
Svaki takav korisnik ili integrator dužan je provesti odgovarajuću i potpunu analizu rizika, procjenu i ispitivanje proizvoda u odnosu na odgovarajuću specifičnu primjenu ili uporabu istog.  
Niti društvo Schneider Electric, Industries SAS niti bilo koje od njegovih povezanih poduzeća ili podružnica neće preuzeti obvezu ili snositi odgovornost za pogrešnu upotrebu ovdje sadržanih informacija.

---

Contractual warranty

---

Warranty period	18 months
-----------------	-----------

---