

## A9A26927

Acti 9 – pomoćni kontakt u slučaju kvara iSD – 1 C/O  
– AC/DC



### Glavno

Range	Acti 9
Product or component type	Fault contact
Device short name	ISD
Signal contacts composition	1 C/O
[In] rated current	1 A at 130 V DC 1.5 A at 60 V DC 2 A at 48 V DC 6 A at 24 V DC 3 A at 415 V AC - 50/60 Hz 6 A at 240 V AC - 50/60 Hz
9 mm pitches	1

### Komplementarno

Range compatibility	Acti 9 iC60 Acti 9 iDPN Vigi Acti 9 iID Acti 9 iC60 RCBO Acti 9 iC65 Acti 9 ARA Acti 9 RCA Acti 9 iDPN (China version) Acti 9 iC40
[U <sub>i</sub> ] rated insulation voltage	4 kV
Local signalling	Mechanical indicator
Mounting mode	Clip-on
Mounting support	DIN rail
Height	86 mm
Width	9 mm
Depth	73 mm
Product weight	33 g
Colour	White
Connections - terminals	Screw clamp terminal 2 cable(s) 2.5 mm <sup>2</sup> rigid Screw clamp terminal 1 cable(s) 0.5...2.5 mm <sup>2</sup> flexible Screw clamp terminal 1 cable(s) 1...4 mm <sup>2</sup> rigid Screw clamp terminal 2 cable(s) 1.5 mm <sup>2</sup> flexible with ferrule
Wire stripping length	10 mm
Tightening torque	1 N.m

### Okolina

standards	EN/IEC 60947-5-1
IP degree of protection	IP20 conforming to EN/IEC 60947-5-1
pollution degree	3 conforming to EN/IEC 60947-5-1
tropicalisation	2 conforming to EN/IEC 60947-5-1
ambient air temperature for operation	-35...70 °C
ambient air temperature for storage	-40...85 °C

### Offer Sustainability

Green Premium product	Green Premium product
-----------------------	-----------------------

Informacije dane u ovoj dokumentaciji sadrže opće opise i/ili tehničke karakteristike o performansama ovdje sadržanih proizvoda.  
 Ova dokumentacija nije namijenjena kao zamjena za niti bi se trebala koristiti za određivanje prikladnosti ili pouzdanosti predmetnih proizvoda za konkretne korisničke primjene.  
 Svaki takav korisnik ili integrator dužan je provesti odgovarajuću i poplunu analizu rizika, procjenu i ispitivanje proizvoda u odnosu na odgovarajuću specifičnu primjenu ili uporabu istog.  
 Niti društvo Schneider Electric Industries SAS niti bilo koje od njegovih povezanih poduzeća ili podružnica neće preuzeti obvezu ili snositi odgovornost za pogrešnu upotrebu ovdje sadržanih informacija.

Compliant - since 1216 - Schneider Electric declaration of conformity    Compliant - since 1216 - Schneider Electric declaration of conformity

Reference not containing SVHC above the threshold	Reference not containing SVHC above the threshold
Available	Available
Available	Available

**Contractual warranty**

Warranty period	18 months
-----------------	-----------