

## A9A26929

Acti 9 – Pomoćni kontakt iOF/SD+OF – 2OC – AC/DC



### Glavno

Range	Acti 9
Product or component type	Double OC or fault contact
Device short name	IOF/SD+OF
Signal contacts composition	2 C/O
[In] rated current	1 A at 130 V DC 1.5 A at 60 V DC 2 A at 48 V DC 6 A at 24 V DC 3 A at 415 V AC - 50/60 Hz 6 A at 240 V AC - 50/60 Hz
9 mm pitches	1

### Komplementarno

Range compatibility	Acti 9 iC60 Acti 9 iDPN Vigi Acti 9 iID Acti 9 iSW-NA Acti 9 iC60 RCBO Acti 9 iC65 Acti 9 ARA Acti 9 RCA Acti 9 iDPN (China version) Acti 9 iC40
[Ui] rated insulation voltage	4 kV
Local signalling	Mechanical indicator
Mounting mode	Fixed
Mounting support	DIN rail
Height	90 mm
Width	9 mm
Depth	73 mm
Product weight	43 g
Colour	White
Connections - terminals	Screw clamp terminal 2 cable(s) 2.5 mm <sup>2</sup> rigid Screw clamp terminal 1 cable(s) 0.5...2.5 mm <sup>2</sup> flexible Screw clamp terminal 1 cable(s) 1...4 mm <sup>2</sup> rigid Screw clamp terminal 2 cable(s) 1.5 mm <sup>2</sup> flexible with ferrule
Wire stripping length	10 mm
Tightening torque	1 N.m

### Okolina

standards	EN/IEC 60947-5-1
tropicalisation	2 conforming to EN/IEC 60947-5-1
ambient air temperature for operation	-35...70 °C
ambient air temperature for storage	-40...85 °C

### Offer Sustainability

Green Premium product	Green Premium product
Compliant - since 1216 - Schneider Electric declaration of conformity	Compliant - since 1216 - Schneider Electric declaration of conformity

Informacije dane u ovoj dokumentaciji sadrže opće opise i/ili tehničke karakteristike o performansama ovdje sadržanih proizvoda. Ova dokumentacija nije namijenjena kao zamjena za niti bi se trebala koristiti za određivanje prikladnosti ili pouzdanosti predmetnih proizvoda za konkretne korisničke primjene. Svaki takav korisnik ili integrator dužan je provesti odgovarajuću i poplunu analizu rizika, procjenu i ispitivanje proizvoda u odnosu na odgovarajuću specifičnu primjenu ili uporabu istog. Niti društvo Schneider Electric, Industries SAS niti bilo koje od njegovih povezanih poduzeća ili podružnica neće preuzeti obvezu ili snositi odgovornost za pogrešnu upotrebu ovdje sadržanih informacija.

Reference not containing SVHC above the threshold	Reference not containing SVHC above the threshold
Available	Available
Available	Available

### Contractual warranty

Warranty period	18 months
-----------------	-----------