

## A9A26946

oslobađanje napona – iMX+OF – jedinica za  
isklapanje – 220..415 V AC



### Glavno

Range	Acti 9
Product or component type	Shunt trip release with OC contact
Device short name	iMX+OF
Signal contacts composition	1 C/O
[Ie] rated operational current	AC-12: 3 A at 415 V AC - 50 Hz AC-12: 6 A at 100 V AC - 50 Hz AC-12: 6 A at 230 V AC - 50 Hz DC-12: 1 A at 110 V DC DC-12: 1 A at 130 V DC
[Uc] control circuit voltage	110...130 V DC 100...415 V AC 50/60 Hz
9 mm pitches	2
Product compatibility	IC60 IID Single terminal Double terminal ISW-NA IDPN Vigi ARA RCA

### Komplementarno

Range compatibility	Acti 9: Acti 9 iDPN (China version) Acti 9: Acti 9 iDPN Vigi Acti 9: Acti 9 iC40 Acti 9: Acti 9 iC65 Acti 9: Acti 9 ARA Acti 9: Acti 9 IID Acti 9: Acti 9 ISW-NA Acti 9: Acti 9 RCA Acti 9: Acti 9 iC60 (double terminals miniature circuit breaker)
Local signalling	Action indicator
Mounting mode	Clip-on
Mounting support	DIN rail
Width	18 mm
Colour	White
Connections - terminals	Clamp terminal 1 cable(s) 6 mm <sup>2</sup> rigid Clamp terminal 2 cable(s) 2.5 mm <sup>2</sup> rigid Clamp terminal 1 cable(s) 4 mm <sup>2</sup> flexible Clamp terminal 2 cable(s) 2.5 mm <sup>2</sup> flexible with cable end cable end
Tightening torque	1 N.m

### Okolina

standards	EN/IEC 60947-5-1
tropicalisation	2 conforming to EN/IEC 60947-5-1
relative humidity	95 % at 55 °C
ambient air temperature for operation	-25...50 °C
ambient air temperature for storage	-40...85 °C

### Offer Sustainability

Green Premium product	Green Premium product
-----------------------	-----------------------

Informacije dane u ovoj dokumentaciji sadrže opće i/ili tehničke karakteristike o performansama ovdje sadržanih proizvoda. Ova dokumentacija nije namijenjena kao zamjena za niti bi se trebala koristiti za određivanje prikladnosti ili pouzdanosti predmetnih proizvoda za konkretne korisničke primjene. Svaki takav korisnik ili integrator dužan je provesti odgovarajuću i poipunu analizu rizika, procjenu i ispitivanje proizvoda u odnosu na odgovarajuću specifičnu primjenu ili uporabu istog. Niti društvo Schneider Electric, Industries SAS niti bilo koje od njegovih povezanih poduzeća ili podružnica neće preuzeti obvezu ili snositi odgovornost za pogrešnu upotrebu ovdje sadržanih informacija.

Compliant - since 1216 - Schneider Electric declaration of conformity	Compliant - since 1216 - Schneider Electric declaration of conformity
Reference not containing SVHC above the threshold	Reference not containing SVHC above the threshold
Available	Available
Need no specific recycling operations	Need no specific recycling operations

**Contractual warranty**

Warranty period	18 months
-----------------	-----------