

A9C15032

impulsni relej iTL+ – 1P+N – 1NO – 16A – zavojnica
230 V AC 50 Hz



Glavno

Range	Acti 9
Product name	Acti 9 iTL+
Product or component type	Impulse relay
Device short name	iTL+
Device application	Standard
Poles description	1P + N
Neutral position	Left
Pole contact composition	1 NO
[In] rated current	16 A
Network type	AC
[Uc] control circuit voltage	230 V AC 50 Hz

Komplementarno

Network frequency	50 Hz
[Ue] rated operational voltage	230 V AC 50 Hz
Control type	Remote and manual control
Control signal type	Impulse
Switching frequency	6 switching operation/minute
Impulse duration	50 ms...1 s
Remote control type	Illuminated push-button 5 mA
Local signalling	ON/OFF indication
Mounting mode	Clip-on
Mounting support	DIN rail
9 mm pitches	2
Height	84 mm
Width	18 mm
Depth	60 mm
Product weight	70 g
Electrical durability	AC-21: 5000000 cycles AC-22: 5000000 cycles
Connections - terminals	Tunnel type terminals top or bottom 2 cable(s) 1.5 mm ² rigid Tunnel type terminals top or bottom 2 cable(s) 1.5 mm ² flexible with ferrule Tunnel type terminals top or bottom 2 cable(s) 2.5 mm ² rigid Tunnel type terminals top or bottom 2 cable(s) 2.5 mm ² flexible without cable end Tunnel type terminals top or bottom 1 cable(s) 4 mm ² rigid Tunnel type terminals top or bottom 1 cable(s) 4 mm ² flexible without cable end
Wire stripping length	10 mm
Tightening torque	1 N.m
Product compatibility	No auxiliary

Okolina

standards	EN 669-2-2
quality labels	NF
noise level	30 dB
IP degree of protection	IP20 on opening conforming to IEC 60529 IP40 in enclosure conforming to IEC 60529
tropicalisation	2 conforming to IEC 60068-1
relative humidity	95 % (55 °C)

Informacije dane u ovoj dokumentaciji sadrže opće opise i/ili tehničke karakteristike o performansama ovdje sadržanih proizvoda.
Ova dokumentacija nije namijenjena kao zamjena za niti bi se trebala koristiti za određivanje prikladnosti ili pouzdanosti predmetnih proizvoda za konkretne korisničke primjene.
Svaki takav korisnik ili integrator dužan je provesti odgovarajuću i potpunu analizu rizika, procjenu i ispitivanje proizvoda u odnosu na odgovarajuću specifičnu primjenu ili uporabu istog.
Niti društvo Schneider Electric, Industries SAS niti bilo koje od njegovih povezanih poduzeća ili podružnica neće preuzeti obvezu ili snositi odgovornost za pogrešnu upotrebu ovdje sadržanih informacija.

ambient air temperature for operation	-5...55 °C
ambient air temperature for storage	-40...60 °C

Offer Sustainability

Not Green Premium product	Not Green Premium product
---------------------------	---------------------------

Contractual warranty

Warranty period	18 months
-----------------	-----------
