



Glavno

Range	Acti 9
Device short name	IATLs
Product or component type	Remote indication auxiliary
Signal contacts composition	1 C/O
Signalling circuit voltage	24 V AC/DC : 10 mA 12...240 V AC : 50/60 Hz 6 A 12...24 V DC : 6 A 15...240 V AC : 50/60 Hz 2 A 13...24 V DC : 2 A
[Uc] control circuit voltage	24...240 V AC 50/60 Hz 24...240 V DC

Komplementarno

Mounting mode	Fixed, on right side of TL
Mounting support	DIN rail
9 mm pitches	1
Height	81 mm
Width	9 mm
Depth	69 mm
Colour	White
Connections - terminals	Tunnel type terminals rigid cable(s) 0.5...4 mm ² Tunnel type terminals rigid cable(s) with cable end 0.5...4 mm ² Tunnel type terminals flexible cable(s) 1...4 mm ² Tunnel type terminals flexible cable(s) with cable end 1...4 mm ²
Wire stripping length	11 mm
Tightening torque	1 N.m
Range compatibility	Acti 9 iTL Acti 9 iTLi Acti 9 iTLs Acti 9 iTLc Acti 9 iTLm
Product compatibility	ITL (16 A) ITL (32 A)
Compatibility code	IATLs

Okolina

tropicalisation	2
relative humidity	95 % (55 °C)
ambient air temperature for operation	-20...50 °C
ambient air temperature for storage	-40...70 °C

Offer Sustainability

Green Premium product	Green Premium product
Compliant - since 1825 - Schneider Electric declaration of conformity	Compliant - since 1825 - Schneider Electric declaration of conformity
Reference not containing SVHC above the threshold	Reference not containing SVHC above the threshold
Available	Available
Need no specific recycling operations	Need no specific recycling operations

Informacije dane u ovoj dokumentaciji sadrže opće opise i/ili tehničke karakteristike o performansama ovdje sadržanih proizvoda.
Ova dokumentacija nije namijenjena kao zamjena za niti bi se trebala koristiti za određivanje prikladnosti ili pouzdanosti predmetnih proizvoda za konkretne korisničke primjene.
Svaki takav korisnik ili integrator dužan je provesti odgovarajuću i potpunu analizu rizika, procjenu i ispitivanje proizvoda u odnosu na odgovarajuću specifičnu primjenu ili uporabu istog.
Niti društvo Schneider Electric Industries SAS niti bilo koje od njegovih povezanih poduzeća ili podružnica neće preuzeti obvezu ili snositi odgovornost za pogrešnu upotrebu ovdje sadržanih informacija.

Contractual warranty

Warranty period

18 months
