



Glavno

Range	Acti 9
Device short name	IATLc+s
Product or component type	Centralized control and remote indication auxiliary
Signal contacts composition	1 C/O
Signalling circuit voltage	24 V AC/DC : 10 mA 12...240 V AC : 50/60 Hz 6 A 12...24 V DC : 6 A 15...240 V AC : 50/60 Hz 2 A 13...24 V DC : 2 A
[Uc] control circuit voltage	24...240 V AC 50/60 Hz

Komplementarno

Mounting mode	Fixed, on right side of TL
Mounting support	DIN rail
9 mm pitches	2
Height	86 mm
Width	18 mm
Depth	71 mm
Colour	White
Connections - terminals	Tunnel type terminals rigid cable(s) 0.5...4 mm ² Tunnel type terminals rigid cable(s) with cable end 0.5...4 mm ² Tunnel type terminals flexible cable(s) 1...4 mm ² Tunnel type terminals flexible cable(s) with cable end 1...4 mm ²
Wire stripping length	11 mm
Tightening torque	1 N.m
Range compatibility	Acti 9 iTL Acti 9 iTLi Acti 9 iTLs
Product compatibility	ITL (16 A) ITL (32 A)
Compatibility code	IATLc+s

Okolina

tropicalisation	2
relative humidity	95 % (55 °C)
ambient air temperature for operation	-20...50 °C
ambient air temperature for storage	-40...70 °C

Offer Sustainability

Green Premium product	Green Premium product
Compliant - since 1825 - Schneider Electric declaration of conformity	Compliant - since 1825 - Schneider Electric declaration of conformity
Reference not containing SVHC above the threshold	Reference not containing SVHC above the threshold
Available	Available
Need no specific recycling operations	Need no specific recycling operations

Contractual warranty

Warranty period	18 months
-----------------	-----------

