



### Glavno

Range	Acti 9
Device short name	IATL4
Product or component type	Step by stel control auxiliary
[Uc] control circuit voltage	230 V AC 50/60 Hz impulse 50 ms

### Komplementarno

Remote control type	Push-button
Step sequences	1st impulse - TL1 on, TL2 off 2nd impulse - TL1 off, TL2 on 3rd impulse - TL1 on, TL2 on 4th impulse - TL1 off, TL2 off
Mounting mode	Fixed, between 2 TL
Mounting support	DIN rail
9 mm pitches	4
Height	86 mm
Width	36 mm
Depth	71 mm
Colour	White
Connections - terminals	Tunnel type terminals rigid cable(s) 0.5...4 mm <sup>2</sup> Tunnel type terminals rigid cable(s) with cable end 0.5...4 mm <sup>2</sup> Tunnel type terminals flexible cable(s) 1...4 mm <sup>2</sup> Tunnel type terminals flexible cable(s) with cable end 1...4 mm <sup>2</sup>
Wire stripping length	11 mm
Tightening torque	1 N.m
Range compatibility	Acti 9 iTL Acti 9 iTLi Acti 9 iTLs Acti 9 iTLc
Product compatibility	ITL (16 A) ITL (32 A)

### Okolina

tropicalisation	2
relative humidity	95 % (55 °C)
ambient air temperature for operation	-20...50 °C
ambient air temperature for storage	-40...70 °C

### Offer Sustainability

Green Premium product	Green Premium product
Compliant - since 1825 - Schneider Electric declaration of conformity	Compliant - since 1825 - Schneider Electric declaration of conformity
Reference not containing SVHC above the threshold	Reference not containing SVHC above the threshold
Available	Available
Need no specific recycling operations	Need no specific recycling operations

---

Contractual warranty

---

Warranty period	18 months
-----------------	-----------

---