

A9C15924

iACT – 24 V DC kontrolni i pomoćni kontakt 1 NO sa sučeljem Ti24 PLC



Glavno

Range	Acti 9
Product or component type	Control and indication auxiliary
Device short name	IACT24
Signal contacts composition	1 NO
Signalling circuit voltage	24 V DC : - 20...20 % 0.002...0.1 A
[Uc] control circuit voltage	24 V DC falling edge 24 V DC rising edge 230 V AC 50/60 Hz maintained >= 200 ms
Control type	Remote control
[Us] rated supply voltage	230 V AC 50/60 Hz

Komplementarno

Mounting mode	Fixed, on the left of CT
Mounting support	DIN rail
Comb busbar and distribution block compatibility	Bottom: YES Top: NO
9 mm pitches	2
Height	81 mm
Width	18 mm
Depth	68 mm
Colour	White
Immunity to microbreaks	10 ms
Undervoltage behaviour	No opening if loss of 24 V DC
Electrical durability	250000 cycles conforming to IEC 60947-5-1
Connections - terminals	Control circuit: tunnel type terminals for 2 flexible cable(s) 2.5 mm ² Control circuit: tunnel type terminals for 2 rigid cable(s) 1.5 mm ² Auxiliary supply: tunnel type terminals for 2 flexible cable(s) 2.5 mm ² Auxiliary supply: tunnel type terminals for 2 rigid cable(s) 1.5 mm ² Control circuit: spring-loaded terminal Ti24 for 2 flexible cable(s) 0.25...0.75 mm ² Control circuit: spring-loaded terminal Ti24 for 1 flexible cable(s) 0.5...1.5 mm ²
Wire stripping length	Control circuit: 10 mm bottom Auxiliary supply: 10 mm bottom Control circuit: 10 mm top
Tightening torque	Control circuit: 1 N.m bottom Auxiliary supply: 1 N.m bottom
Product compatibility	With PLC ICT 220 V 50 Hz ICT 230/240 V 50 Hz ICT 220/240 V 50 Hz Acti 9 Smartlink
Compatibility code	IACT24

Okolina

standards	IEC 60947-1 annex S
quality labels	CE
IP degree of protection	IP20 conforming to IEC 60529 IP40 (in modular enclosure) conforming to IEC 60529
pollution degree	3 conforming to IEC 60439-1
tropicalisation	2 conforming to IEC 60947-5-1

Informacije dane u ovoj dokumentaciji sadrže opće opise i/ili tehničke karakteristike o performansama ovdje sadržanih proizvoda. Ova dokumentacija nije namijenjena kao zamjena za niti bi se trebala koristiti za određivanje prikladnosti ili pouzdanosti predmetnih proizvoda za konkretne korisničke primjene. Svaki takav korisnik ili integrator dužan je provesti odgovarajuću i potpunu analizu rizika, procjenu i ispitivanje specifičnu primjenu ili uporabu istog. Niti društvo Schneider Electric Industries SAS niti bilo koje od njegovih povezanih poduzeća ili podružnica neće preuzeti obvezu ili snositi odgovornost za pogrešnu upotrebu ovdje sadržanih informacija.

relative humidity	93 % (40 °C) conforming to IEC 60068-2
ambient air temperature for operation	-25...60 °C
ambient air temperature for storage	-40...80 °C

Offer Sustainability

Green Premium product	Green Premium product
Compliant - since 1312 - Schneider Electric declaration of conformity	Compliant - since 1312 - Schneider Electric declaration of conformity
Reference not containing SVHC above the threshold	Reference not containing SVHC above the threshold
Available	Available
Available	Available

Contractual warranty

Warranty period	18 months
-----------------	-----------